



180 Dutton Avenue
 Buffalo, NY 14211
 www.wellworthproducts.com
 1-800-890-7935
 Date Prepared: 12/17/07

IV² PURGE™ Fuel Injector Cleaner

DESCRIPTION

IV² Purge™ is the professional solution for eliminating such problems as hesitation, stalling, hard starting, loss of power and poor mileage in late model and finely tuned cars. Powerful in-line cleaners quickly dissolve carbon and other deposits from intake valves, fuel injectors and the combustion chamber. Works equally well in all U.S. and imported cars. Can pressure may be regulated to over 100 lbs., meeting all O.E.M specifications. Safe on oxygen sensors and catalytic converters. A special lubricant and anti-corrosive agent have been added to IV² Purge™ to protect the fuel injectors, engine and exhaust system during cleaning. Complete adapter tool kit #999 available.

USES

Cleans: • Fuel Injectors • Intake Valves • Combustion Chambers

DIRECTIONS

IMPORTANT: ALWAYS WEAR SAFETY GLASSES. WEARERS OF CONTACT LENSES SHOULD REMOVE THEM BEFORE USING THIS PRODUCT. PROTECT PAINTED SURFACES FROM ACCIDENTAL CONTACT. NOTE: USE IV² PURGE ON GASOLINE ENGINES ONLY. DURING USE, CAN MUST BE IN AN UPSIDE DOWN POSITION AT ALL TIMES, EVEN WHEN ATTACHING THE REGULATOR VALVE. 1. Please refer to our instruction manual for specific instructions on the correct adapters, hookups and can pressures for the model car you are cleaning. Before engine is restarted after cleaning, add a bottle of XCELERATE™ to the gas tank to cleanse the system of any remaining cleaner. 2. IV² Purge™ used in conjunction with our Top Shot™, Master Blaster™ and Xcelerate™ is a very effective system for cleaning up the most stubborn deposits and offers a less expensive and time saving alternative to replacing injectors or walnut shell blasting. Ask your Well•Worth® distributor for details on this complete cleaning system.

PACKAGING

1031 - 20 oz.
 Aerosol Can
12 Per Case
 WW 5 K Kit
 IV²Purge, Power Up,
 Top Shot 6 oz.

STORAGE

Keep away from heat, sparks and flame. Keep from freezing. Do not puncture, incinerate or burn.

SPECIFICATIONS

FLASH POINT : 12° F
 EVAPORATION RATE : Faster Than
 (Butyl Acetate = 1)
 COLOR : Light Yellow
 ODOR : Amine
 SOLUBILITY IN WATER : Complete

HMIS HAZARD RATING

0-Least	A-Goggles	HEALTH	1
1-Slight	B-Goggles, Gloves	FLAMMABILITY	3
2-Moderate	C-Goggles, Gloves, Protective Wear	REACTIVITY	0
3-High		PERSONAL PROTECTION	B
4-Extreme			

FIRST AID MEASURES

EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.
 SKIN CONTACT: Immediately flush skin with plenty of water. Remove clothing. Get medical attention immediately.
 Wash clothing separately before reuse. INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. INGESTION: Get medical attention immediately. If swallowed, do NOT induce vomiting. Give victim a glass of water or milk. Call a physician or poison control center immediately. ChemTrec (USA) 800-424 9300.

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product.

ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.