



180 Dutton Avenue
 Buffalo, NY 14211
 www.wellworthproducts.com
 1-800-890-7935
 Date Prepared: 2/18/08

SUB ZERO™ Air Conditioning Lubricant

DESCRIPTION

Sub Zero™ is a technologically advanced formula that is compatible with all A/C systems. Whether yours is an R-12 or R-134a system, Sub Zero™ will lubricate and reduce critical compressor wear. Acid is neutralized, and moisture removed from all PAG, ester, paraffin and mineral based oil. The friction modifiers included in this oil reduces compressor-operating noise. Leaks will be easily detected with a black light because of the fluorescent dye package. Cooling efficiency is restored to all systems.

USES

- Reduce Compressor Wear and Noise
- Remove Moisture
- Restore Cooling efficiency

DIRECTIONS

Have an experienced technician administer the appropriate amount of Sub Zero™ air conditioning system lubricant and dye. 1. Check the entire system for leaks, using a black light.

STORAGE

Do not store in temperatures above 120°F (50°C). Store away from direct heat source and strong oxidizing agents.

PACKAGING

3014 - 2 oz.
 Liquid Bottle
 12 Per Case

SPECIFICATIONS

FLASH POINT : Product; 464°F
 EVAPORATION RATE : Greater Than 1
 (Water = 1)
 COLOR : Transparent Green Color
 ODOR : Characteristic Solvent
 SOLUBILITY IN WATER : Negligible

HMIS HAZARD RATING

0-Least	A-Goggles	HEALTH	1
1-Slight	B-Goggles, Gloves	FLAMMABILITY	1
2-Moderate	C-Goggles, Gloves,	REACTIVITY	0
3-High	Protective Wear	PERSONAL PROTECTION	B
4-Extreme			

FIRST AID MEASURES

EYE CONTACT: Flush from eyes with copious amounts of water. SKIN CONTACT: Wash with soap and water. INHALATION: Move to fresh air. INGESTION: Do not induce vomiting due to danger of aspirating fluid into lungs. Get medical attention immediately. ChemTrec (USA) 800-424 9300.

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product.

ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.