



180 Dutton Avenue
 Buffalo, NY 14211
 www.wellworthproducts.com
 1-800-890-7935
 Date Prepared: 3/16/08

PRISMA™ Acrylic Enamel Paints

DESCRIPTION

Professional formula provides superior coverage in a durable finish that won't crack, chip or peel. Use on metal, wood, fiberglass, automotive engines or anywhere a quality coating is desired. Prisma paints are lead free and have no ozone depleting chemicals. Fast dry formula enables you to touch painted surfaces in as little as 15-20 minutes. Also available in special colors such as Cummins Beige (#4010), Cast Iron Gray (#4011) and NC Yellow (#4009). All paints come in 16 oz. aerosol cans.

USES

Use On: • Metal • Wood • Fiberglass • Automotive Engines

DIRECTIONS

1. IMPORTANT: NEVER SPRAY ON HOT PARTS (ENGINES, ETC.). 2. Surface To be painted must be clean and dry. Remove all grease, grime, oil, etc, using a solvent cleaner such as Well-Worth's TASKMASTER™ or similar solvent material. Remove all rust. 3. SHAKE WELL. Mixing ball must move freely for about one minute. Repeat this procedure periodically during application. 4. Use at room temperature (approximately 70°F). 5. Mask off all areas that are not to be painted. 6. Holding can about 10-12 inches from surface, spray in smooth even strokes. Use a side to side motion and release spray head after each stroke. Overlap adjacent painted areas for a continuous finish. 7. TWO THIN COATS ARE BETTER THAN ONE HEAVY COAT. Second coat should be applied immediately. 8. When finished spraying, clean valve by turning can upside down and spraying until only pressure escapes. 9. To clean a clogged spray head, remove from can. Carefully clean intake slot by scraping clean with a knife. Orifice can be unplugged by scraping dried paint off with a knife or by inserting a fine wire into opening. If these measures are unsuccessful, spray head can be soaked in paint thinner.

PACKAGING

- # 4001 - Gloss Black
 - # 4002 - Flat Black
 - # 4003 - S-Gloss Black
 - # 4004 - Clear
 - # 4005 - Gloss White
 - # 4006 - Aluminum
 - # 4007 - Dull Aluminum
- 16 oz. Aerosol Cans
 12 Per Case

STORAGE

Do not store in temperatures above 120°F (50°C). Do not puncture, incinerate or burn. Do not place near sources of heat. Protect from direct sunlight. Do not warehouse in subfreezing temperatures.

SPECIFICATIONS

FLASH POINT : Propellant; -40°F, Product; 0°F
 EVAPORATION RATE (Water = 1) : Greater Than 1
 COLOR : All Varieties
 ODOR : Solvent Odor
 SOLUBILITY IN WATER : None

HMIS HAZARD RATING

0-Least	A-Goggles	HEALTH	1
1-Slight	B-Goggles, Gloves	FLAMMABILITY	4
2-Moderate	C-Goggles, Gloves, Protective Wear	REACTIVITY	3
3-High		PERSONAL PROTECTION	A
4-Extreme			

FIRST AID MEASURES

EYE CONTACT: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
 SKIN CONTACT: Generally the product does not irritate the skin. INHALATION: In case of unconsciousness, place patient in side position for transportation. Supply fresh air. If necessary, provide artificial respiration. Consult a doctor if symptoms persist. INGESTION: Consult a doctor if symptoms persist. ChemTrec (USA) 800-424 9300.

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product.

ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.