



PACKAGING

4008 - 16 oz.
Aerosol Can
12 Per Case



180 Dutton Avenue
Buffalo, NY 14211
www.wellworthproducts.com
1-800-890-7935
Date Prepared: 2/18/08

1ST KOTE™ Sandable Primer

DESCRIPTION

1st Kote™ is a high quality flexible primer for all types of flexible and rigid surfaces. Specially formulated to etch its way into urethane parts for extra strong adhesion. Super fast dry time allows 1st Kote™ to be sanded to a perfect featheredge in 5 minutes. Won't clog paper. 1st Kote's neutral gray color makes recoating with any paint a snap. By gradually applying 1st Kote™ in light, even coats, even deep scratches can be repaired.

USES

Use on all Flexible and rigid surfaces such as: • Plastics • Metals • Fiberglass • Wood

DIRECTIONS

1. For best results, spray at room temperature (approximately 70°F). 2. Remove all grease, oil, dirt, corrosion, etc. from surfaces to be primed. Make sure surface is clean and dry before proceeding. 3. Mask off adjacent areas to protect from over spray. 4. SHAKE CAN WELL. Mixing ball must move freely for about 1 minute. Repeat shaking periodically during use. 5. Holding can about 8-10 inches from surface to be primed, spray in smooth even strokes. Use a side to side motion and release spray head after each stroke. Overlap adjacent painted areas. TWO THIN COATS ARE BETTER THAN ONE Heavy Coat 6. When finished spraying, clean valve by turning can upside down and spraying until only pressure escapes. 7. To clean a clogged spray head, remove from can, clean intake slot by scraping clean with a knife. Orifice can be unplugged by scraping dried primer off with a knife, inserting a fine wire into the opening or soak spray head in paint thinner. After cleaning spray head, turn can upside down and spray to clear out valve and spray head.

STORAGE

Do not store in temperatures above 120°F (50°C). Do not puncture, incinerate or burn. Do not place near sources of heat or direct sunlight. Do not warehouse in subfreezing temperatures.

SPECIFICATIONS

FLASH POINT : Product; -2°F
EVAPORATION RATE : Greater Than 1 (Water = 1)
COLOR : Gray
ODOR : Solvent Odor
SOLUBILITY IN WATER : Negligible

HMIS HAZARD RATING			
0-Least	A-Goggles	HEALTH	1
1-Slight	B-Goggles, Gloves	FLAMMABILITY	4
2-Moderate	C-Goggles, Gloves, Protective Wear	REACTIVITY	3
3-High		PERSONAL PROTECTION	A
4-Extreme			

FIRST AID MEASURES

EYE CONTACT: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
SKIN CONTACT: Wash skin with soap and fresh water. Generally the product does not irritate the skin.
INHALATION: Supply fresh air; consult doctor in case of complaints. INGESTION: After swallowing; Consult a doctor if symptoms persist. ChemTrec (USA) 800-424 9300.

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product.

ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.