



PACKAGING

7002 - 16 oz.
Aerosol Can
12 Per Case



180 Dutton Avenue
Buffalo, NY 14211
www.wellworthproducts.com
1-800-890-7935
Date Prepared: 2/17/08

FIRE-UP™ Premium Engine Starting Fluid

DESCRIPTION

Fire Up's high quality ether formula assures fast starting of cold gasoline and diesel engines anytime of year. Contains anti-corrosive additives and upper cylinder lube. Meets DOT. regulations.

USES

Use Fire Up to get you going in hard starting engines when the following adverse conditions exist: • Wet, cold freezing weather (starts down to -65°F). • Weak batteries. • For diesels with low compression or low cetane fuels. • Use in automobiles, trucks, buses, farm and garden engines, motorcycles and outboard motors.

DIRECTIONS

1. CAUTION: DO NOT USE WITH GLOW PLUGS. DO NOT INHALE. 2. Before starting engine, hold can in an upright position and spray Fire-Up™ for two seconds into air cleaner, air intake or carburetor. Continue spraying for a few seconds after engine starts running. Avoid excessive application.

STORAGE

Extremely flammable. Store and use away from all heat and ignition sources. Use adequate ventilation. Do not store in temperatures above 120°F (50°C). Do not puncture, incinerate or burn.

SPECIFICATIONS

FLASH POINT : Product; -49°F
EVAPORATION RATE : Ether 37.5
(Butyl Acetate = 1)
COLOR : Clear
ODOR : Ether Odor
SOLUBILITY IN WATER : Slight

HMIS HAZARD RATING			
0-Least	A-Goggles	HEALTH	2
1-Slight	B-Goggles, Gloves	FLAMMABILITY	4
2-Moderate	C-Goggles, Gloves,	REACTIVITY	1
3-High	Protective Wear	PERSONAL PROTECTION	B
4-Extreme			

FIRST AID MEASURES

EYE CONTACT: Flush with water for 15 minutes. If irritation persists, call physician. SKIN CONTACT: Flush with water for 15 minutes. If irritation persists, call physician. INHALATION: Remove to fresh air. If breathing has stopped, give artificial respiration. INGESTION: Do not induce vomiting, call physician immediately. ChemTrec (USA) 800-424 9300.

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product.

ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.