



180 Dutton Avenue
 Buffalo, NY 14211
 www.wellworthproducts.com
 1-800-890-7935
 Date Prepared: 10/30/07

SUMMIT™ Total Diesel Fuel Treatment

Clean Diesel Additive

DESCRIPTION

The ultimate hi-tech fuel additive and anti-gel for the cold weather treatment of diesel fuels. SUMMIT™ is the everything-in-one package treatment needed to produce "Premium Diesel Fuel", exceeding the requirements needed under NCWM's Premium Diesel Fuel Standards & Tests. Using SUMMIT™ as directed with straight #2 Diesel fuel will give you greater protection to a lower temperature for less than the cost of blended fuel. Plus, you can get more energy, mileage and power, and many other benefits from using SUMMIT™ with straight #2 Diesel fuel. Why spend the extra money for blended fuel when SUMMIT™ can do more for less cost?

USES

- Create a Premium Diesel Fuel
- Remove Water from Fuel
- Improve Cetane Rating
- Improves Lubricity of Low and Ultra Low Sulfur Fuels
- Improve Fuel Atomization
- Clean Fuel Injectors and Pumps
- Prevent Fuel from "Gelling" and Fuel Line Freeze-ups
- Lower CFPP and CP by up to 40°F

DIRECTIONS

For best results, use every time you fuel, adding contents to fuel tank(s) prior to fueling. The fueling process will then ensure that complete and proper mixing takes place. Use SUMMIT™ on a regular basis to obtain all the benefits listed above under "USES". Treatment ratio is 1:1000 which equals 32 oz. per 250 gallons, or 1 gallon per 1000 gallons of fuel. First time users can use a ratio of 1:500 which is 32 oz. per 125 gallons, or 1 gallon per 500 gallons of fuel to further lower CFPP and PP and to speed the cleaning process. When operating in extreme conditions (i.e. extreme cold, marine, high humidity, poor quality fuel), it is acceptable to use 32 oz. per 125 gallons (1:500) on a regular basis.

PACKAGING

- # 8054 - 12 oz. Bottle
24 Per Case
- # 8042 - 32 oz.
12 Per Case
- # 8043 - 1 gallon
4 Per Case
- # 8044 - 5 gallon
- # 8045 - 55 gallon
- # 8045t - 275 gallon

STORAGE

Store at room temperature. Do not store near potential sources of ignition. Store in well ventilated area.

SPECIFICATIONS

- FLASH POINT : Product; 145°F
- EVAPORATION RATE (Butyl Acetate = 1) : Slower
- COLOR : Amber
- ODOR : Sweet Odor
- SOLUBILITY IN WATER : Slight

HMIS HAZARD RATING

0-Least	A-Goggles	HEALTH	2
1-Slight	B-Goggles, Gloves	FLAMMABILITY	2
2-Moderate	C-Goggles, Gloves, Protective Wear	REACTIVITY	0
3-High		PERSONAL PROTECTION	B
4-Extreme			

FIRST AID MEASURES

EYE CONTACT: Flush with large amounts of water for 15 minutes. SKIN CONTACT: Wash with soap and water. Wash clothing separately before reuse. INHALATION: Remove victim to fresh air. INGESTION: DO NOT induce vomiting. Get medical attention. ChemTrec (USA) 800-424 9300.

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product.

ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.