



180 Dutton Avenue
 Buffalo, NY 14211
 www.wellworthproducts.com
 1-800-890-7935
 Date Prepared: 1/12/08

OCTI-PLUS™ Multi-Functional Gas Additive

DESCRIPTION

Multi-functional gas additive provides excellent cleaning for carburetors, port fuel injectors, direct injection fuel systems, intake valves and combustion chamber deposits. Octi-Plus™ is considered an "A" rated corrosion inhibitor to reduce engine and storage tank corrosion. Also, inhibits growth of bacteria and fungi in fuel, plus slows sludge formation in engine oil. Octi-Plus™ is much more effective in solving water problems in fuel than traditional methanol or isopropyl "dry gases". Octi-Plus™ completely eliminates water through dispersion technology. Octi-Plus will disperse (eliminate) 75% of its own volume of water. EPA and CARB approved.

USES

- Improves Mileage and Performance
- Improves starting, drivability, and performance of all gasoline engines
- Eliminates water
- Prevents sludge and varnish formulation
- Reduces Emissions
- FOR ALL FUELS, INCLUDING ETHANOL BLENDED FUELS
- STOPS CHEMICAL BREAKDOWN OF COMPONENTS CAUSED BY ETHANOL (GASOHOL).

DIRECTIONS

FOR FUEL SYSTEMS: Pour entire bottle into gas tank before adding fuel to ensure thorough mixing. 12 oz. treats up to 30 gal. (1 oz. to 2.5 gal.). Run engine briefly to cycle product through the system. **NOTE:** Not for use in Diesel Fuel. **FOR STORAGE TANKS:** For best results, use each time you add fuel to the tank, adding to tank prior to unloading fuel. The fuel delivery process will ensure that complete and proper mixing takes place. **NOTE:** Bulk sizes use a different treatment ratio (approximately 1 oz. to 12 gal.). Use 1 gal. for each 1500 gal. of fuel (1:1500 ratio). First time users can use 1 gal. for each 750 gal. to speed the cleaning process. Octi-Plus will disperse (eliminate) 75% of its own volume of water.

PACKAGING

- # 8056 - 12 oz. Bottle
24 Per Case
- # 8051 - 1 gallon
4 Per Case
- # 8052 - 5 gallon
- # 8053 - 55 gallon
- Bulk sizes available.

STORAGE

Store at room temperature. Do not store near potential sources of ignition. Store in well ventilated area.

SPECIFICATIONS

FLASH POINT : Product; 112° F
 EVAPORATION RATE (Butyl Acetate = 1) : Slower
 COLOR : Light Amber
 ODOR : Sweet Ammine Odor
 SOLUBILITY IN WATER : Slight

HMIS HAZARD RATING

0-Least	A-Goggles	HEALTH	2
1-Slight	B-Goggles, Gloves	FLAMMABILITY	2
2-Moderate	C-Goggles, Gloves, Protective Wear	REACTIVITY	0
3-High		PERSONAL PROTECTION	B
4-Extreme			

FIRST AID MEASURES

EYE CONTACT: Flush with large amounts of water for 15 minutes. **SKIN CONTACT:** Wash with soap and water. Wash clothing separately before reuse. **INHALATION:** Remove victim to fresh air. **INGESTION:** DO NOT induce vomiting. Get medical attention. ChemTrec (USA) 800-424 9300.

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product.

ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.