



Body Guard™ UNDERCOATING

DESCRIPTION

Body Guard™ is an outstanding undercoat that contains no asbestos fiber and is fast drying. High-density rubberized formula dries to touch in about an hour. Leaves behind a tough, flexible coating that will not crack, chip or peel under harsh conditions. Provides superior salt protection and sound deadening. Body Guard™ can be used both on plastic and metal surfaces.

USES

- Undercoats: underbody panels; frames; inner fenders; doors on cars, trucks, and trailers.
- Post and Wood Preserver
- Tree wound Dressing
- Eaves, Troughs, and Flashing Sealer.
- Concrete and Asphalt Driveway Crack Sealer.

PACKAGING

9001 - 24 oz.
Aerosol Can
12 Per Case

DIRECTIONS

1. Surface to be treated must be clean and dry.
2. SHAKE WELL BEFORE USING. Allow mixing ball to move freely for about one minute before using. Repeat this procedure periodically during application.
3. Hold can 8-10 inches from surface and spray in smooth even strokes. If a thicker coating and coarse texture is desired, hold can closer during application. For a smooth finish, hold can further away.
4. BODY GUARD™ dries in about 1 hour. CANNOT BE PAINTED OVER.
5. Remove any over spray with WellWorth TASK MASTER™ cleaning solvent, kerosene or mineral spirits.
6. Clear valve after spraying by turning can upside down and spray until only pressure escapes.

STORAGE

Do not store in temperatures above 120°F (50°C). Do not puncture, incinerate or burn can. Do not place near sources of heat.

SPECIFICATIONS

HEALTH	: 2	FLASH POINT	: -40°F
FLAMMABILITY	: 4	EVAPORATION RATE (Water = 1)	: Greater than 1
REACTIVITY	: 0	COLOR	: Black Viscous
PERSONAL PROTECTION	: B	ODOR	: Solvent Odor
		SOLUBILITY IN WATER	: None

CALL TOLL FREE: 1-800-890-7935 OR VISIT OUR WEB SITE: www.wellworthproducts.com