



**PACKAGING**

#8017 - 64 oz.  
 10 Per Case  
 (Also available in bulk)



180 Dutton Avenue  
 Buffalo, NY 14211  
 www.wellworthproducts.com  
 1-800-890-7935  
 Date Prepared: 2/26/10

**SYNTHETIC POWER STEERING FLUID and Conditioner**

**DESCRIPTION**

Well•Worth Synthetic Power Steering Fluid and Conditioner is a premium quality fully synthetic fluid specially formulated to meet or exceed the warranty requirements of all major manufacturers of most automobiles and truck power steering systems. Our fluid is designed to minimize sludge and varnish deposits, eliminate squeals and provide smoother quieter performance. Well•Worth Synthetic Power Steering Fluid resists foaming, oxidation, corrosion and rusting. This fluid provides excellent wear protection to extend power steering system life and is compatible with all power steering fluids.

**USES**

- Helps keep Power Steering Systems running smooth and quiet.
  - Meets or Exceeds O.E.M. Performance Specifications for the Following:
- |                         |                               |                                 |                                |
|-------------------------|-------------------------------|---------------------------------|--------------------------------|
| <b>GM 9985010</b>       | <b>Ford M2C195-A</b>          | <b>Audi P/N G002000</b>         | <b>Volkswagen P/N G002000</b>  |
| <b>GM 9985835</b>       | <b>Honda P/N 08206-9002PE</b> | <b>Mercedes P/N 00 989 8803</b> | <b>Volkswagen TL VW 570 26</b> |
| <b>Chrysler MS-1872</b> | <b>Delphi 5099</b>            | <b>Saab P/N 30 09 800</b>       | <b>Navistar TMS 6811</b>       |
| <b>Chrysler MS-5931</b> | <b>Hyundai PF-3</b>           | <b>Subaru P/N K0209A0080</b>    | <b>AMC C4124</b>               |

**DIRECTIONS**

Shut off engine. Add Power Steering Fluid to specified level. Do not overfill. Check reservoir regularly and refill as needed. (Check the machine manufacturers specifications when adding the 64 oz. Power Steering Fluid during the flush procedure).

**STORAGE**

Keep containers closed when not in use. Store in a cool, well ventilated area. Do not handle or store near heat, flame or strong oxidants.

**SPECIFICATIONS**

FLASH POINT : Product; 455 F, (235 C)  
 EVAPORATION RATE : N/A  
 POUR POINT : -120 F, (-49 C)  
 COLOR : Amber Liquid  
 ODOR : Petroleum Odor  
 SOLUBILITY IN WATER : None  
 BROOKFIELD VISCOSITY : 8,700

HMIS HAZARD RATING			
0-Least	A-Goggles	HEALTH	1
1-Slight	B-Goggles, Gloves	FLAMMABILITY	1
2-Moderate	C-Goggles, Gloves, Protective Wear	REACTIVITY	0
3-High		PERSONAL PROTECTION	B
4-Extreme			

**FIRST AID MEASURES**

EYE CONTACT: Immediately flush with cool water for at least 15 minutes. Do not let victim rub eyes.  
 SKIN CONTACT: Flush with large amount of water. Use soap if possible. Remove contaminated clothing and wash before reuse. If irritation persists, seek medical attention.  
 INHALATION: Remove to fresh air. If not breathing give artificial respiration, preferably mouth to mouth. If breathing is difficult give oxygen. Get medical attention.  
 INGESTION: Do not induce vomiting. Give water to dilute. Never give anything by mouth if the victim is unconscious or having convulsions. Contact physician immediately. ChemTrec (USA) 800-424 9300.

*NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product.*

ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.