



PACKAGING

1062 - 6 oz.
 # 1034 - 20 oz.
 Aerosol Can
12 Per Case
 WW 1 K Kit
 Master Blaster,
 Top Shot 6 oz., Power Up



180 Dutton Avenue
 Buffalo, NY 14211
 www.wellworthproducts.com
 1-800-890-7935
 Date Prepared: 11/24/07

MASTER BLASTER™ Intake Valve Cleaner

DESCRIPTION

Driveability problems associated with carbon build-up are quickly and simply resolved with MASTER BLASTER™. Especially recommended for finely tuned fuel injected engines. Equally effective as a top engine cleaner for standard engines. Driveability problems such as knocking, pinging and after-dieseling are immediately improved as Master Blaster™ disintegrates carbon deposits from piston crowns, cylinder heads and combustion chamber.

USES

- Cleans: Piston Crowns • Intake Valves • Combustion Chambers

DIRECTIONS

1. Start engine and bring up to operating temperature. 2. Adjust engine idle to about 500 RPM and remove PCV valve from engine. If PCV is screwed into the engine, disconnect hose from PCV valve. 3. Attach snorkel to MASTER BLASTER™ can and spray through the PCV valve or disconnected hose for 3 minutes. When spraying cleaner through hose, RPM'S may have to be increased. Adjust accordingly. 4. Turn engine off and replace PCV valve or hose. NOTE: To clean carburetor and combustion chamber. have warm engine at about 750 RPM. Remove air cleaner and spray entire can down the throat of the carburetor, making certain to clean all components. Shut off engine for 10 minutes to allow the product to do its work. To complete the job, start the engine and blow out deposits.

STORAGE

Do not store in temperatures above 120°F (50°C). Do not puncture, incinerate or burn. Do not place near sources of heat.

SPECIFICATIONS

FLASH POINT : Propellant; -40°F, Product; >100°F
 EVAPORATION RATE : Faster
 (Water = 1)
 COLOR : Colorless
 ODOR : Characteristic Solvent Odor
 SOLUBILITY IN WATER : Almost Clear

| HMIS HAZARD RATING | | | |
|--------------------|---------------------------------------|---------------------|---|
| 0-Least | A-Goggles | HEALTH | 2 |
| 1-Slight | B-Goggles, Gloves | FLAMMABILITY | 3 |
| 2-Moderate | C-Goggles, Gloves, Protective Wear | REACTIVITY | 0 |
| 3-High | | PERSONAL PROTECTION | A |
| 4-Extreme | | | |

FIRST AID MEASURES

EYE CONTACT: Wash eyes with fresh water. If irritation continues, contact physician. SKIN CONTACT: Wash skin with soap and fresh water. If irritation continues, contact physician. INHALATION: Remove to fresh air. Give oxygen. Contact physician. INGESTION: Do not induce vomiting-gastric lavage. Contact physician. ChemTrec (USA) 800-424 9300.

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product.

ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.