



180 Dutton Avenue
 Buffalo, NY 14211
 www.wellworthproducts.com
 1-800-890-7935
 Date Prepared: 11/8/07

Clean Diesel Additive

FREEZE FLOW™ Hi-Tech Cold Weather Diesel Fuel Treatment and Conditioner

DESCRIPTION

FREEZE FLOW™ is the cold weather treatment to prevent fuel gelling, waxing, fuel line freeze-up, improve fuel efficiency, increase power, reduce emissions, reduce engine wear, stabilize fuel, and eliminate the harmful effects of water in the fuel. FREEZE FLOW™ is also a powerful fuel system cleaner. It dissolves the gum, varnish, and carbon deposits that distort fuel injector spray patterns and damage delicate injector and pump components. FREEZE FLOW™ uses a combination of an organic solvent and an organic polymer that significantly depresses the PP (Pour Point) and lowers the CFPP (Cold Filter Plug Point) by inhibiting the growth of wax crystal within the fuel. Without FREEZE FLOW™ wax crystals form lattices and grow together to solidify (gel) the fuel. Using FREEZE FLOW™ with straight #2 fuel can actually cost significantly less than blended fuel and you get all of the many other benefits listed above.

PACKAGING

- # 8021 - 32 oz.
12 Per Case
- # 8022 - 1 gallon
4 Per Case
- # 8023 - 5 gallon
- # 8024 - 55 gallon
- # 8024† - 275 gallon

USES

- Cetane Improver • Lower Cold Filter Plug Point • Cleans Fuel Injectors and Pumps
- Reduce Oxidation to Stabilize Fuel • Eliminate Water • Improve Fuel Atomization

DIRECTIONS

For best results, use every time you fuel, adding contents to fuel tanks prior to fueling. The fueling process will ensure that complete and proper mixing takes place. Use 32 oz. for each 250 gallons of fuel (1:1000 treatment ratio). First time users or below 0°F you can use 32 oz. for each 125 gallons to improve fuel flow and speed the cleaning process. When operating in extreme conditions (very cold weather) it is acceptable to use the 32 oz. per 125 gallons dosage on a regular basis.

STORAGE

Store at room temperature. Do not store near potential sources of ignition. Store in well ventilated area.

SPECIFICATIONS

- FLASH POINT : Product; 108°F
- EVAPORATION RATE (Butyl Acetate = 1) : Slower
- COLOR : Amber
- ODOR : Sweet Odor
- SOLUBILITY IN WATER : Slight

HMIS HAZARD RATING

0-Least	A-Goggles	HEALTH	1
1-Slight	B-Goggles, Gloves	FLAMMABILITY	2
2-Moderate	C-Goggles, Gloves, Protective Wear	REACTIVITY	1
3-High		PERSONAL PROTECTION	B
4-Extreme			

FIRST AID MEASURES

EYE CONTACT: Flush with large amounts of water for 15 minutes. SKIN CONTACT: Wash with soap and water. Wash clothing separately before reuse. INHALATION: Remove victim to fresh air. INGESTION: DO NOT induce vomiting. Get medical attention. ChemTrec (USA) 800-424 9300.

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product.

ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.