



180 Dutton Avenue
 Buffalo, NY 14211
 www.wellworthproducts.com
 1-800-890-7935
 Date Prepared: 11/29/07

Clean Diesel Additive

ONE-4-ALL™ with LUBRICITY Four Season Diesel Fuel Treatment

DESCRIPTION

ONE-4-ALL™ with LUBRICITY is the all-season treatment for diesel and other fuels to restore the lubricity to low and ultra low sulfur fuels, improve fuel efficiency, increase power, reduce emissions, reduce engine wear, stabilize fuel, and eliminate the harmful effects of water in the fuel. ONE-4-ALL™ with LUBRICITY is an organic based product that will cause the lubricity of low and ultra low sulfur fuels to meet or exceed B.O.C.L.E. and or H.F.R.R. requirements. ONE-4-ALL™ with LUBRICITY dissolves gum, varnish, and carbon deposits that distort injector spray patterns and damage components.

USES

- Cleans Fuel Injectors and Pumps
- Improves Fuel Atomization for Greater Efficiency and More Power
- Removes Water From Fuel

DIRECTIONS

For best results, use every time you fuel, adding contents to fuel tank(s) prior to fueling. The fueling process will then ensure that complete and proper mixing takes place. Treatment ratio is 1:1000 which equals 32 oz. per 250 gallons, or 1 gallon per 1000 gallons of fuel. First time users can use a ratio of 1:500 which is 32 oz. per 125 gallons, or 1 gallon per 500 gallons of fuel to speed the cleaning process. When operating in extreme conditions (i.e. extreme cold, marine, high humidity, poor quality fuel), it is acceptable to use 32 oz. per 125 gallons (1:500) on a regular basis. ONE-4- ALL™ with LUBRICITY will eliminate approximately one half its own volume in water. For cold weather operation with ONE 4 ALL™ with LUBRICITY additive, we suggest the use of SUMMIT™ – Total Diesel Treatment.

PACKAGING

- # 8033 - 32 oz.
12 Per Case
- # 8034 - 1 gallon
4 Per Case
- # 8035 - 5 gallon
- # 8036 - 55 gallon
- # 8036t - 275 gallon

STORAGE

Store at room temperature. Do not store near potential sources of ignition. Store in well ventilated area.

SPECIFICATIONS

FLASH POINT	: Product; 145°F
EVAPORATION RATE (Butyl Acetate = 1)	: Slower
COLOR	: Amber
ODOR	: Sweet Odor
SOLUBILITY IN WATER	: Slight

HMIS HAZARD RATING

0-Least	A-Goggles	HEALTH	2
1-Slight	B-Goggles, Gloves	FLAMMABILITY	2
2-Moderate	C-Goggles, Gloves, Protective Wear	REACTIVITY	0
3-High		PERSONAL PROTECTION	B
4-Extreme			

FIRST AID MEASURES

EYE CONTACT: Flush with large amounts of water for 15 minutes. SKIN CONTACT: Wash with soap and water. Wash clothing separately before reuse. INHALATION: Remove victim to fresh air. INGESTION: DO NOT induce vomiting. Get medical attention. ChemTrec (USA) 800-424 9300.

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product.

ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.