



Description:

IV² PURGE™ is the professional solution for eliminating such problems as hesitation, stalling, hard starting, loss of power and poor mileage in late model and finely tuned cars. Powerful in-line cleaners quickly dissolve carbon and other deposits from intake valves, fuel injectors and the combustion chamber. Works equally well in all U.S. and imported cars. Can pressure may be regulated to over 100 lbs., meeting all O.E.M specifications. Safe on oxygen sensors and catalytic converters. A special lubricant and an anti-corrosive agent have been added to IV² PURGE™ to protect the fuel injectors, engine and exhaust system during cleaning.

IV² PURGE™ Fuel Injector Cleaner

Directions:

IMPORTANT: ALWAYS WEAR SAFETY GLASSES. WEARERS OF CONTACT LENSES SHOULD REMOVE THEM BEFORE USING THIS PRODUCT. PROTECT PAINTED SURFACES FROM ACCIDENTAL CONTACT. NOTE: USE IV² PURGE ON GASOLINE ENGINES ONLY. DURING USE, CAN MUST BE IN AN UPSIDE DOWN POSITION AT ALL TIMES, EVEN WHEN ATTACHING THE REGULATOR VALVE

1. Please refer to our instruction manual for specific instructions on the correct adapters, hookups and can pressures for the model car you are cleaning. Before engine is restarted after cleaning, add a bottle of one of our fuel treatments (XCELERATE™, POWER UP™ or OCTI-PLUS™) to the gas tank to cleanse the system of any remaining cleaner.
2. IV² PURGE™ used in conjunction with our TOP SHOT™, MASTER BLASTER™ and one of our fuel treatments is a very effective system for cleaning up the most stubborn deposits and offers a less expensive and time saving alternative to replacing injectors or walnut shell blasting. Ask your Well•Worth® distributor for details.

Uses:

Cleans:

- Fuel Injectors
- Combustion Chambers
- Intake Valves

Packaging:

#1031 - 20 oz. Aerosol Can.....12 per case
 #1052 Liquid - 12 oz. Can (for VT 1636 Canister use).....12 per case
 WW 5 K Kit - IV² PURGE™ (#1031), POWER UP™ (#8003), TOP SHOT™ (#1059)
 NOTE: HMIS Health rating for #1052 Liquid is 1.

For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

Do not store in temperatures above 120°F (50°C). Do not puncture, incinerate or burn. Keep away from heat, sparks or open flame. Keep from freezing.

First Aid Measures:

- EYE CONTACT: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.
- SKIN CONTACT: Immediately flush skin with plenty of water. Remove clothing. Get medical attention. Wash clothing separately before reuse.
- INHALATION: Remove to fresh air, give oxygen or artificial respiration as needed. Get medical attention.
- INGESTION: DO NOT induce vomiting. Give victim a glass of water or milk. Get medical attention.

ChemTrec (USA) 800-424-9300

HMIS HAZARD RATING

0-Least	A-Goggles	Health..... 2
1-Slight	B-Goggles, Gloves	Flammability..... 3
2-Moderate	C-Goggles, Gloves	Reactivity..... 0
3-High	Protective Wear	Personal Protection..... B
4-Extreme		

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product. ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.