



Description:

EXCEL™ is a copper rich formula that provides superior lubrication and protection under the most adverse and corrosive conditions. Assures accurate torquing and easier assembly and disassembly of parts. Superior formulation is not affected by acids, solvents, oils, alkalies, gasoline, salt water, and other chemicals. Maintains a higher degree of electrical conductivity. For use on plastics, fiberglass and all metals (including all alloys of steel, aluminum, brass and copper). Packaged with a bilingual label (English/French).

EXCEL™ Heavy Duty Anti-Seize Lubricant

Directions:

FOR BEST RESULTS ALL SURFACES MUST BE CLEAN AND FREE OF GREASE.

1. SHAKE CAN WELL BEFORE USE.
2. Spray EXCEL™ to completely cover part.
3. Assemble part.
4. Follow manufacturer's specs when accurate torquing is required.
5. When job is completed, clean valve by inverting the can and spraying until only pressure escapes.

Uses:

- Automotive
- Farm
- Couplings
- Oxygen Sensor Threads
- Conduit Connections
- Brake Lube Assembly
- Manifold Studs
- Industry
- Cylinder Head Bolts
- Spark Plugs
- EGR Fittings
- Gears
- Roller and Hinge
- Engine Head, Starter and Alternator Bolts
- Marine
- Bushings
- Splines
- Drive Chains
- Sprockets
- Lever Pivots

Packaging:

#3009 - 12 oz. Aerosol Can.....12 per case

For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

Do not store in temperatures above 120°F (50°C). Do not puncture, incinerate or burn. Do not place near sources of heat.

First Aid Measures:

- EYE CONTACT: Flush eyes with water for at least 15 minutes. If irritation continues, get medical attention.
- SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing and launder before reuse. If irritation continues, get medical attention.
- INHALATION: Remove to fresh air. Give artificial respiration or oxygen, as needed. Get medical attention.
- INGESTION: Get medical attention immediately. Do NOT induce vomiting. Give victim a glass of water or milk.

ChemTrec (USA) 800-424-9300

HMIS HAZARD RATING

0-Least	A-Goggles	Health..... 2
1-Slight	B-Goggles, Gloves	Flammability..... 4
2-Moderate	C-Goggles, Gloves	Reactivity..... 0
3-High	Protective Wear	Personal Protection..... A
4-Extreme		

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product. ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.