



**Description:**

ICE BREAKER™ is a unique combination of three of organic solvents that dissolve Wax and Ice Crystals that cause fuel to gel. When used as directed, ICE BREAKER™ will begin to work within 20 minutes to completely re-liquefy all the fuel throughout the entire system. ICE BREAKER™ contains NO chlorinated solvents, methanol or other harmful alcohols. ICE BREAKER™ is effective with #1, #2, #4 and #6 fuels.

**Clean Diesel Additive**

This diesel fuel additive complies with the federal low sulfur content requirements for use in diesel motor vehicles (on-road) and non-road engines.

**ICE BREAKER™ Emergency Treatment for Gelled Diesel and Biodiesel Fuels**

**Directions:**

For best results, remove fuel filters and fill 1/2 full of ICE BREAKER™ and 1/2 full of diesel fuel, reinstall filters and pour balance of suggested treatment into fuel tanks. Use at a treatment ratio of 1:200 (32 oz. for every 50 gallons of fuel). Allow 20 minutes for product to dissolve waxed fuel.  
NOTE: ICE BREAKER™ IS FOR EMERGENCY USE (GELLED FUEL) ONLY, it is not meant to and should not be used on a regular or ongoing basis.

**Uses:**

- Dissolves Wax
- Works on Diesel and Biodiesel Fuel
- Breakdown and Disperse Water.

**Packaging:**

#8046 - 32 oz. Bottle.....12 per case

For complete product specifications, review the product SDS at [wellworthproducts.com](http://wellworthproducts.com).

**Storage:**

Keep containers closed when not in use. Do not handle or store near heat, flame or strong oxidants.

**First Aid Measures:**

- EYE CONTACT: Flush with large amounts of water for 15 minutes.
- SKIN CONTACT: Wash with soap and water.
- INHALATION: Remove person to fresh air.
- INGESTION: Do not induce vomiting. Get medical attention.

**ChemTrec (USA) 800-424-9300**

**HMIS HAZARD RATING**

0-Least	A-Goggles	Health.....	2
1-Slight	B-Goggles, Gloves	Flammability.....	3
2-Moderate	C-Goggles, Gloves	Reactivity.....	1
3-High	Protective Wear	Personal Protection.....	B
4-Extreme			

**NOTICE TO PURCHASER:** Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product. **ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.**