



1ST KOTE SANDABLE PRIMER



1ST KOTE™ is a high quality flexible primer for all types of flexible and rigid surfaces. Specially formulated to etch its way into urethane parts for extra strong adhesion. Super fast dry time allows 1ST KOTE™ to be sanded to a perfect featheredge in 5 minutes. Won't clog paper. 1ST KOTE's neutral gray color makes recoating with any paint a snap. By gradually applying 1ST KOTE™ in light, even coats, even deep scratches can be repaired.

Directions:

1. For best results, spray at room temperature (approximately 70°F).
2. Remove all grease, oil, dirt, corrosion, etc. from surfaces to be primed. Make sure surface is clean and dry before proceeding.
3. Mask off adjacent areas to protect from over spray.
4. SHAKE CAN WELL. Mixing ball must move freely for about 1 minute. Repeat shaking periodically during use.
5. Holding can about 8-10 inches from surface to be primed, spray in smooth even strokes. Use a side-to-side motion and release spray head after each stroke.
6. When finished sprayed, clean valve by turning can upside down and spraying until only pressure escapes.

Product Number and Packaging:
#4008 – Net wt. 12 oz Aer.....12 per case

For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

Do not store in temperatures above 120°F (50°C). Do not puncture, incinerate or burn. Do not place near sources of heat. Keep from freezing.

First Aid Measures:

- EYE CONTACT: Rinse open eye for several minutes under running water. If symptoms persist, get medical attention.
- SKIN CONTACT: Remove contaminated clothing. Wash exposed area with soap and water.
- INHALATION: If breathing is difficult, administer oxygen. Get medical attention.
- INGESTION: Get medical attention immediately.

ChemTrec (USA) 800-424-9300

800-890-7935

www.wellworthproducts.com