



DOT 3 BRAKE FLUID™ SUPER HEAVY DUTY



DOT 3 super heavy duty brake fluid exceeds SAE Spec J1703, Federal Spec W-B-680, and conforms to Federal Motor Vehicle Safety Standard 116. Exceeds 450°F boiling point. Reduces wear on system components. Add to flush machine reservoir during flush service or to brake fluid reservoir when level gets low. Service kits are available, packaged with your favorite size and type brake cleaner. These kits may be used with our brake fluid flush machine.

Directions:

FOLLOW VEHICLE MANUFACTURER RECOMMENDATIONS WHEN ADDING BRAKE FLUID. KEEP BRAKE FLUID CLEAN AND DRY. Contamination with dirt, water, petroleum products or other materials may result in brake failure or costly repairs. Clean all dirt from cylinder and surrounding area before removing reservoir cap.

Product Number and Packaging:

- #8070 – 12 oz.....24 per case
- #8717 – 32 oz.....12 per case
- #8017 – gal.....4 per case

For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

Store In a dry place in its original container. Keep container clean and tightly closed.

First Aid Measures:

- EYE CONTACT: Immediately flush eyes with water for at least 15 minutes. Seek immediate medical attention.
- SKIN CONTACT: Immediately flush skin with water while removing contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Destroy contaminated clothing articles.
- INHALATION: Move person to fresh air; if effects occur, get medical attention.
- INGESTION: Do not induce vomiting. Seek medical attention immediately.

ChemTrec (USA) 800-424-9300