




CHAIN GANG™

CHAIN AND CABLE LUBRICANT



CHAIN GANG™ with foaming action ensures maximum penetration. The water-resistance formula reduces friction and wear, eliminates corrosion and withstands extreme temperatures. Regular use extends the working life of equipment and improves performance. Perfect for use on bicycles, motorcycles, cables and pulleys, chains, gears and sprockets.

Directions:

1. IMPORTANT: CHAIN GANG™ SHOULD NEVER BE APPLIED WHEN EQUIPMENT IS IN USE. PROPER PROTECTIVE MEASURES SHOULD BE USED TO ENSURE THAT EQUIPMENT CANNOT BE STARTED UNTIL TREATMENT IS COMPLETED.
2. Shake can well before using. Spray at room temperature in a well-ventilated area.
3. Prior to applying CHAIN GANG™, dirty chains can be flushed clean with either Well Worth's PREDATOR™ carburetor cleaner or BRAKE AWAY™ brake cleaner.
4. Holding can in an upright position, spray generously to completely saturate and protect the surfaces being treated. Re-apply as required.

Product Number and Packaging:

#5008 - Net wt. 12.75 oz. Aer.....12 per case

For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

Do not store above 120°F (50°C). Do not puncture, incinerate or burn. Keep away from heat, sparks or open flame.

First Aid Measures:

- EYE CONTACT: Wash eyes with fresh water. If irritation continues, get medical attention.
- SKIN CONTACT: Wash skin with fresh water. If irritation continues, get medical attention.
- INHALATION: Remove to fresh air. Give oxygen. Get medical attention.
- INGESTION: Do not induce vomiting-gastric lavage. Get medical attention.

ChemTrec (USA) 800-424-9300

800-890-7935

www.wellworthproducts.com