



# EXCEL™

## HEAVY DUTY ANTI-SEIZE LUBRICANT



EXCEL™ Brush Top Can is a copper-rich formula that contains graphite complex grease and provides superior lubrication and protection under the most adverse and corrosive conditions. Assures accurate torquing and easier assembly and disassembly of parts. Superior formulation is not affected by acids, solvents, oils, alkalis, gasoline, salt water and other chemicals. Maintains a higher degree of electrical conductivity. For use on plastics, fiberglass and all metals (including all alloys of steel, aluminum, brass and copper).

### Directions:

FOR BEST RESULTS ALL SURFACES MUST BE CLEAN AND FREE OF GREASE.

1. To activate can, twist off round protrusion on the Yorker brush. Turn Yorker brush 90°.
2. Slip black handles under tabs and depress to start flow of product.
3. Apply a light coating of compound to parts.
4. Assemble parts.
5. Wipe away excess compound.

### Product Number and Packaging:

#6010 – Net wt. 3.75 oz. Brush Top Can.....12 per case

For complete product specifications, review the product SDS at [wellworthproducts.com](http://wellworthproducts.com).

### Storage:

Do not store near open flame or other sources of ignition.

### First Aid Measures:

- EYE CONTACT: Flush eyes with water for at least 15 minutes. If irritation continues, get medical attention.
- SKIN CONTACT: Wash skin with soap and water. Remove contaminated clothing and launder before reuse. If irritation continues, get medical attention.
- INHALATION: Remove to fresh air. If irritation continues, get medical attention.
- INGESTION: Do not induce vomiting. Keep warm, get medical attention.

ChemTrec (USA) 800-424-9300

800-890-7935

[www.wellworthproducts.com](http://www.wellworthproducts.com)