



FLASH PLUS™ HIGH GLOSS SILICONE COATING



FLASH PLUS™ solvent silicone coating conditions any vinyl or rubber surface fast. Saves time and minimizes waste because FLASH PLUS™ is ready to use and requires no mixing. FLASH PLUS™ contains more silicone glossifiers than our popular FLASH™ coating for a higher sheen and longer-lasting finish.

Directions:

INTERIORS:

1. Moisten a clean applicator sponge with FLASH PLUS™ and wipe on vinyl and rubber surfaces.
2. Allow to dry or wipe dry with a clean cloth.

TIRES:

1. Spray or wipe FLASH PLUS™ directly on tire.
2. Allow to dry or wipe dry with a clean cloth.

NOTE: To avoid slippery surfaces, do not apply to seat bottoms, steering wheel or foot pedals.

Product Number and Packaging:

#204832 – 32 oz.

#20481 – 1 gallon

#20485C – 5 gallons

For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

Keep away from heat or flame. Do not allow product to freeze. Keep container closed when not in use.

First Aid Measures:

- **EYE CONTACT:** Flush eyes with cool water for at least 15 minutes, or flush with buffered eye wash solution. If irritation continues, get medical attention.
- **SKIN CONTACT:** Wash with soap and water. Remove clothing and wash before reuse.
- **INHALATION:** Remove to fresh air, insure breathing.
- **INGESTION:** Drink large amounts of water or milk. Seek prompt medical attention.

ChemTrec (USA) 800-424-9300