



GUZZLER™ SOLVENT CLEANER



GUZZLER™ is a ready-to-use solvent cleaner that can be used on exteriors to remove tar and bug splatter, or under the hood to remove tough baked-on grease, sludge and oil from engines, transmissions and power trains. Guzzler can also be used on garage floors to remove grease and oil.

Directions:

EXTERIORS:

1. Spray Guzzler liberally onto tar or bug splatter on the painted surface.
2. Allow soils to soften, then wipe away.
3. Wash treated areas with car soap and water.

UNDER HOOD:

1. For a thorough cleaning, make certain engine is warm (not hot).
2. Turn ignition off before proceeding.
3. Remove air cleaner. Cover distributor cap and carburetor with waterproof material (e.g. plastic sandwich bags).
4. Using trigger or Chapin sprayer, liberally spray Guzzler in all areas to be cleaned.

5. Allow product to dwell for approximately 5 minutes before hosing off with a strong stream of water.

GARAGE FLOORS/DRIVEWAYS:

1. Spray Guzzler liberally on area to be cleaned.
2. Let product dwell for 10 minutes before hosing off with a strong stream of water.

Product Number and Packaging:

- | | |
|--------------------|--------------------|
| #1013 – 1 gallon | #1014 – 5 gallons |
| #1015 – 15 gallons | #1016 – 55 gallons |

For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

Keep away from children. Keep away from heat/sparks/open flames/hot surfaces. No smoking.

First Aid Measures:

- **INHALATION:** If breathing is difficult or irritating, move person to fresh air immediately.
- **SKIN CONTACT:** Rinse area with soap and water.
- **EYE CONTACT:** Flush immediately with large amounts of clean water for a minimum of 15 minutes, lifting upper and lower lids occasionally. Do not rub eyes. If any irritation persists, seek medical attention.
- **INGESTION:** If swallowed, do not induce vomiting: seek medical advice.

ChemTrec (USA) 800-424-9300