




THUNDERBOLT™ PENETRATING OIL



Thunderbolt's formula works by attracting it to metals, rust and corrosion, working to free frozen parts quickly and easily. THUNDERBOLT™ foams on and stays on so it won't run off. Keeps working even when exposed to high temperatures. THUNDERBOLT™ is formulated with a special lubricant that protects and lubricates metal surfaces even under demanding conditions.

Directions:

1. SHAKE CAN BEFORE USING.
 2. Spray THUNDERBOLT™ on frozen, rusted or oxidized part.
 3. In extremely tough situations, repeat the above procedure.
- NOTE: For greater accuracy, or when working in tight areas, use the attached extension tube.

For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

Do not store in temperatures above 120°F (50°C). Do not puncture, incinerate or burn. Do not place near sources of heat. Keep out of sunlight.

First Aid Measures:

- EYE CONTACT: Flush eyes with water for at least 15 minutes. If irritation persists, get medical attention.
- SKIN CONTACT: Wash hands and skin with soap and fresh water. If irritation continues, get medical attention.
- INHALATION: If person is unconscious move to fresh air and administer oxygen until emergency personnel arrive.
- INGESTION: If swallowed do not induce vomiting. Use gastric lavage. Get immediate medical attention.

Product Number and Packaging:

#5009 – Net wt. 15.75 oz. Aer.....12 per case

ChemTrec (USA) 800-424-9300