



# VERSA LUBE™

SILICONE DIELECTRIC COMPOUND AND BRAKE LUBE



Now, with just the touch of a finger, you can quickly and easily lubricate or seal with VERSA LUBE's 100% silicone-based grease. Outperforms and outlasts traditional petroleum, synthetic and lithiums. VERSA LUBE™ maintains superior lubrication and adhesion on all metal parts even when exposed to such adverse conditions as water, high heat (resistant to over 750°F) or chemicals. Excellent as a brake system lubricant and an electrical connection treatment. Many other uses for automotive, industrial and marine, aviation and farm.

**Directions:**

1. Make certain surface is clean and dry before applying VERSA LUBE™. If necessary, thoroughly clean area with one of Well Worth's shop solvents or brake cleaners.
2. Spread an even coat of VERSA LUBE™ on surface to lubricate or seal. Wipe off excess.

For complete product specifications, review the product SDS at [wellworthproducts.com](http://wellworthproducts.com).

**Storage:**

Store in a cool, well-ventilated area at temperatures below 120°F (50°C). Do not store in direct sunlight. Do not puncture, incinerate or burn can.

**First Aid Measures:**

- EYE CONTACT: Flush eyes with plenty of water for at least 15 minutes and get medical attention.
- SKIN CONTACT: Remove completely with a dry cloth or paper towel before washing with detergent and water. Get medical attention if irritation develops.
- INHALATION: Remove to fresh air.
- INGESTION: No first aid should be needed. Note to physicians: None known.

**Product Number and Packaging:**

#6007 – Net wt. 3 oz.....12 per case

ChemTrec (USA) 800-424-9300