



PEARLESCENCE™ 1 Step Cleaner/Wax/Protector

Directions:

HIGH SPEED BUFFER: While the product is wet, buff area with a high speed buffer and a polishing pad. Keep the pad flat on the painted surface and buff until product is dry.

ORBITAL BUFFER OR BY HAND: Apply a small amount of product onto the painted surface using a wax applicator. Allow to dry to a haze. Remove residue with a soft polishing cloth or dry bonnet.

- 1. Shake container well before using.
- 2. Make sure surface is cool to touch.
- 3. Use a moist wax applicator to apply PEARLESCENCE™ to a 2' x 2' area.

Uses:

• Ideal for New and Used Car Finishes, Airplanes and Marine Surfaces

Packaging:

#205732 - 32 oz. #20571 - 1 Gallon For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

Avoid sparks and open flames. Keep container closed when not in use. Do not allow product to freeze. Keep out of reach of children

First Aid Measures:

- EYE CONTACT: Flush eyes with cool water for at least 15 minutes, or flush with a buffered eye wash solution. If irritation persists, get medical attention.
- SKIN CONTACT: Wash with soap and water. Remove clothing and wash before reuse.
- INHALATION: Remove to fresh air and insure breathing.
- INGESTION: Get prompt medical attention.

ChemTrec (USA) 800-424-9300

HMIS HAZARD RATING

4-Extreme

0-Least**A**-Goggles**1**-Slight**B**-Goggles, Gloves**2**-Moderate**C**-Goggles, Gloves**3**-HighProtective Wear

Protection B

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product. ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.