

## POLY GUARD<sup>TM</sup> POLYMER PAINT SEALANT



## **Directions:**

For best results, do not use in direct sunlight. Make sure the surface is clean and dry before applying POLY GUARD™.

1. Using a damp applicator pad, apply a thin coat of POLY GUARD™ directly to the surface. Work in 2' x 2' sections.

2. After product has dried, remove using a micro fiber towel.

Product Number and Packaging: #213232 - 32 oz. #21321 - 1 Gallon For complete product specifications, review the product SDS at wellworthproducts.com.

Storage: Do not store below 32 degrees F. Do not store in direct sunlight. Keep away from heat, open flames or other sources of ignition. Keep away from children. Keep containers tightly closed. First Aid Measures:

EYE CONTACT: Flush immediately with large amounts of clean water for a minimum of 15 minutes, lifting upper and lower lids occasionally. Do not rub eyes. If any irritation persists, seek medical attention. SKIN CONTACT: Rinse area with soap and water.

INHALATION: If breathing is difficult or irritating, move person to fresh air

INGESTION: Do not induce vomiting. If the person is conscious, give two glasses of water to dilute the ingested material. Follow up with several glasses of fruit juice or very dilute vinegar or carbonated soda to neutralize the alkaline material. Small amounts that may have accidentally entered the mouth should be rinsed out thoroughly with water. Seek medical attention immediately.

Chemtrec (USA) 800-424-9300