

A2Z[™] ALL-PURPOSE LUBRICANT



Directions:

- 1. IMPORTANT: Make certain the ignition is off and cool before spraying engines or equipment. Allow a couple of minutes for "drying" action to take place before turning ignition back on.
- 2. SHAKE WELL. Spray on surface to be treated. Use handy extension tube for hard-to-reach places or pinpoint applications.
- 3. NOTE: A2Z™ is safe on painted surfaces, plastics, glass, rubber and fabrics. Clear non-silicone, non-gummy formula is easily removed with any petroleumbased solvent.

Product Number and Packaging: #5010 – Net wt. 14.5 oz V.O.C. Aer......12 per case For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

Do not store in temperatures above 120°F (50°C). Do not puncture, incinerate or burn. Do not place near sources of heat. Keep away from electrical current or battery terminals.

First Aid Measures:

- EYE CONTACT: Wash eyes with fresh water. If irritation continues, get medical attention.
- SKIN CONTACT: Wash skin with fresh water. If irritation continues, get medical attention.
- INHALATION: Remove to fresh air. Give oxygen. Get medical attention
- INGESTION: Do not induce vomiting. Get medical attention.

ChemTrec (USA) 800-424-9300