

POWERUP[™] FUEL SYSTEM CLEANER



Directions:

Add one bottle, 12 oz., of POWERUP™ to fuel tank. 12 oz. treats up to 50 gallons. For best results, add POWERUP™ when you will be driving non-stop at highway speeds for at least 20 minutes. Contains no harmful alcohols, will not harm catalytic converters or oxygen sensors.

For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

Do not store in temperatures above 120°F (50°C). Keep away from heat, sparks or open flame.

First Aid Measures:

- EYE CONTACT: Flush with large amounts of cool water for 15 minutes. If irritation persists, get medical attention.
- SKIN CONTACT: Wash with soap and water and rinse thoroughly.
 Immediately remove contaminated clothing and launder before reuse. Discard shoes and other leather articles saturated with the material.
- INHALATION: Remove person to fresh air. If breathing is difficult, get medical attention.
- INGESTION: Do not induce vomiting. Give water or milk to dilute, get medical attention.

ChemTrec (USA) 800-424-9300

Product Number and Packaging: #8003 – 12 fluid oz......24 per case