



# FREEZE FLOW™ Hi-Tech Cold Weather Diesel Fuel Treatment and Conditioner

### **Directions:**

For best results, use every time you fuel. Adding product to fuel tank prior to fueling will speed the treatment process.

Use 32 oz. for each 250 gallons of fuel (1:1000 treatment ratio). When operating below zero, use 32 oz. for each 125 gallons (1:500 treatment ratio) to provide additional cold weather protection

#### **Uses:**

- Lower Cold Filter Plug Point
- Cleans Fuel Injectors and Pumps
- Eliminate Water

- Cetane Improver
- Reduce Oxidation to Stabilize Fuel
- Improve Fuel Atomization

## Packaging:

#8024t - 275 Gallon

#8021 - 32 oz. Bottle	12 per case
#8022 - 1 Gallon	4 per case
#8023 - 5 Gallon	
#8024 - 55 Gallon	

For complete product specifications, review the product SDS at wellworthproducts.com.

## Storage:

Store at room temperature. Do not store near potential sources of ignition. Store in well ventilated area.

## First Aid Measures:

- EYE CONTACT: Flush with large amounts of water for 15 minutes.
- SKIN CONTACT: Wash with soap and water.
- INHALATION: Remove person to fresh air.
- INGESTION: Do not induce vomiting. Get medical attention.

ChemTrec (USA) 800-424-9300

### HMIS HAZARD RATING

TIMIO TIALLA ID TIATING		
<b>0</b> -Least	<b>A</b> -Goggles	Health1
<b>1</b> -Slight	<b>B</b> -Goggles, Gloves	Flammability2
<b>2</b> -Moderate	<b>C</b> -Goggles, Gloves	Reactivity1
<b>3</b> -High	Protective Wear	Personal
<b>4</b> -Extreme		ProtectionB

NOTICE TO PURCHASER: Welle Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product. ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.