



SUMMIT™ CONCENTRATED TOTAL DIESEL FUEL TREATMENT



SUMMIT™ Total Diesel Treatment is our premium year-round fuel treatment. SUMMIT™ provides a high level of anti-gelling protection, cleans fuel injectors, increases cetane, adds lubricity and removes water in all diesel fuels.

Directions:

SUMMIT™ is designed to be used in all diesel fuels year-round.

SUMMIT™ should be added to fuel at a ratio of:

- 12 oz. to 100 gallons of fuel
- 32 oz. to 250 gallons of fuel
- 1 gallon to 1000 gallons of fuel
- 55 gallons to 55,000 gallons of fuel

For cold weather operation, SUMMIT™ provides a high level of anti-gel protection. In extreme cold weather (below 0°F) it is acceptable to use a ratio of 12 oz. to 25 gallons of fuel.

To enhance proper mixing, add SUMMIT™ prior to filling fuel tank.

Product Number and Packaging:

- #804212 – 12 fluid oz.....24 per case
- #8042 – 32 fluid oz.....12 per case
- #8043 – 1 gallon.....4 per case

For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

Store at temperatures above 32°F. Do not store near potential sources of ignition. Store in well-ventilated areas.

First Aid Measures:

- EYE CONTACT: Flush with large amounts of water for 15 minutes.
- SKIN CONTACT: Wash with soap and water.
- INHALATION: Remove person to fresh air.
- INGESTION: Do not induce vomiting. Get medical attention.

ChemTrec (USA) 800-424-9300