



**Description:**

Antifreeze, just like other fluids in your vehicle, becomes depleted of essential additives over time if not properly maintained. KOOL WELL™ Radiator Conditioner not only replaces depleted inhibitors, but also adds a long lasting alkaline reserve to the coolant. KOOL WELL™ protects against pitting, scaling and other corrosion damage to the cooling system. Formula provides maximum heat transfer and protects all metal and aluminum parts in most cooling systems. Contains a water pump lubricant. KOOL WELL™ mixes safely with all antifreeze coolants, will not harm hose connections or metals in the cooling system when used as directed.



**Extra Performance**

**KOOL WELL™ Super Radiator Conditioner**

**Directions:**

DO NOT REMOVE RADIATOR CAP WHILE ENGINE IS HOT.

1. With the engine off and cool, remove radiator cap.
2. Be certain water level is at least 2 inches below the overflow level.
3. Shake bottle well. Add entire bottle of KOOL WELL™. Treats up to 22 quarts.
4. Replace radiator cap. Start engine and run for 10 minutes after reaching operating temperature to mix completely.

NOTE: For proper preventative maintenance, add every 6 months or when added protection is desired.

**Uses:**

- Restores Essential Inhibitors in Coolant.
- Prolongs Cooling System Life.

**Packaging:**

#8004 - 12 oz. Bottle.....24 per case  
WW 19 K Kit - Kool Well™, Flush Well™ (#8007 - 12 oz.), Stop Well™ (#8005 - 12 oz.)

For complete product specifications, review the product SDS at [wellworthproducts.com](http://wellworthproducts.com).

**Storage:**

No special handling procedures. Store at room temperature.

**First Aid Measures:**

- EYE CONTACT: Flush with large amounts of water for 15 minutes, holding eyelids open during flushing with water. Get medical attention.
- SKIN CONTACT: Wash with soap and water, then flush with water until all chemical is removed. Remove contaminated clothing promptly and wash before reuse. If irritation persists get medical attention.
- INHALATION: Remove to fresh air. If breathing is difficult, get oxygen or seek medical attention.
- INGESTION: Drink large amounts of water or acidic drinks. DO NOT induce vomiting, Get immediate medical attention.

**ChemTrec (USA) 800-424-9300**

**HMIS HAZARD RATING**

0-Least	A-Goggles	Health..... 2
1-Slight	B-Goggles, Gloves	Flammability..... 0
2-Moderate	C-Goggles, Gloves	Reactivity..... 0
3-High	Protective Wear	Personal Protection..... B
4-Extreme		

**NOTICE TO PURCHASER:** Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product. **ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.**