



**Description:**

Over time, almost all cooling systems develop a build-up of scale, rust or other corrosion by-products. Left untouched, even a minimal build-up on heat transfer surfaces can radically affect the performance of the cooling system. Scale and rust build-up restrict coolant flow, resulting in overheating and eventually engine damage and breakdown. FLUSH WELL™ quickly restores most cooling systems to like new performance by flushing harmful scale deposits, grease, oil residue and rust in just one application. FLUSH WELL™ is completely harmless to all cooling system components. No neutralizer is needed after using FLUSH WELL™.



**Extra Performance**

**FLUSH WELL™ Cooling System Super Flush**

**Directions:**

DO NOT REMOVE RADIATOR CAP WHILE ENGINE IS HOT.

1. With the engine off and cool, remove radiator cap. Drain cooling system. Close drain and refill system with clean water.
2. Shake contents of FLUSH WELL™ and pour into cold radiator.
3. Replace radiator cap to closed position and start engine. Turn heater on and set controls to maximum settings. After engine has reached normal operating temperature, run engine between 10 and 30 minutes.
4. After radiator has cooled, drain system and flush with clean water until water draining from block and radiator is clear.
5. Refill with anti-freeze, water and Well•Worth's Kool Well™ Radiator Conditioner, following label instructions.

NOTE: For use with power flush machines, follow equipment manufacturers instructions.

**Uses:**

Quickly and Safely Removes:

- Scale
- Rust
- Other Deposits

**Packaging:**

#8007 - 12 oz. Bottle.....24 per case  
WW 19 K Kit - Flush Well™, Kool Well™ (#8004 - 12 oz.), Stop Well™ (#8005 - 12 oz.)

For complete product specifications, review the product SDS at [wellworthproducts.com](http://wellworthproducts.com).

**Storage:**

Do not store in temperatures exceeding 120°F (50°C). Do not store in automobiles. Store at room temperature.

**First Aid Measures:**

- EYE CONTACT: Flush with large amounts of water for 15 minutes, holding eyelids open during flushing with water. Get medical attention.
- SKIN CONTACT: Wash with soap and water, then flush with water until all chemical is removed. Remove contaminated clothing promptly and wash before reuse. If irritation persists get medical attention.
- INHALATION: Remove to fresh air.
- INGESTION: Drink large amounts of water to dilute. DO NOT INDUCE VOMITING. Get medical attention.

**ChemTrec (USA) 800-424-9300**

**HMIS HAZARD RATING**

0-Least	A-Goggles	Health..... 1
1-Slight	B-Goggles, Gloves	Flammability..... 0
2-Moderate	C-Goggles, Gloves	Reactivity..... 0
3-High	Protective Wear	Personal Protection..... B
4-Extreme		

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product. ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.