



Description:

ONE 4 ALL™ with LUBRICITY is an all season diesel fuel treatment that eliminates water and increases the lubricity (H.F.R.R) of the fuel to meet or exceed engine manufacturers recommended levels. This extra lubricity is vital to long term reliability and minimization of wear related failures. ONE 4 ALL™ with LUBRICITY also helps dissolve gums, varnishes, and carbon deposits that form in the fuel system leading to distorted injector spray patterns and/or component damage.

Clean Diesel Additive

This diesel fuel additive complies with the federal low sulfur content requirements for use in diesel motor vehicles (on-road) and non-road engines.

ONE 4 ALL™ with LUBRICITY All Season Diesel Fuel Treatment and Conditioner

Directions:

For best results, use every time you fuel, adding contents to fuel tank(s) prior to fueling will ensure complete and proper mixing takes place.

Treatment ratio is 1:1000 which equals 32 oz. per 250 gallons, or 1 gallon per 1000 gallons of fuel.

First time users can use a ratio of 1:500 which is 32 oz. per 125 gallons, or 1 gallon per 500 gallons of fuel to speed the cleaning process.

When operating in extreme conditions (i.e. extreme cold, marine, high humidity, poor quality fuel), it is acceptable to use 32 oz. per 125 gallons (1:500) on a regular basis.

ONE 4 ALL™ with LUBRICITY will eliminate approximately one half its own volume in water. For cold weather operation with ONE 4 ALL™ with LUBRICITY additive, we suggest the use of our SUMMIT™ – Total Diesel Treatment product.

Uses:

- Provides Required Lubrication...Lacking in Ultra-Low Sulfur Diesel Fuel
- Cleans Fuel Injectors and Pumps
- Improves Fuel Atomization for Greater Efficiency and More Power
- Removes Water From Fuel

Packaging:

- #8033 - 32 oz. Bottle.....12 per case
- #8034 - 1 Gallon.....4 per case
- #8035 - 5 Gallon
- #8036 - 55 Gallon
- #8036t - 275 Gallon

For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

Store at room temperature. Do not store near potential sources of ignition. Store in well ventilated area.

First Aid Measures:

- EYE CONTACT: Flush with large amounts of water for 15 minutes.
- SKIN CONTACT: Wash with soap and water.
- INHALATION: Remove person to fresh air.
- INGESTION: Do not induce vomiting. Get medical attention.

ChemTrec (USA) 800-424-9300

HMIS HAZARD RATING

0-Least	A-Goggles	Health.....2
1-Slight	B-Goggles, Gloves	Flammability.....2
2-Moderate	C-Goggles, Gloves	Reactivity.....0
3-High	Protective Wear	Personal Protection.....B
4-Extreme		

NOTICE TO PURCHASER: Well-Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product. **ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.**