



# BLACK BEAUTY™

SOLVENT-BASED NON-SILICONE RUBBER TREATMENT



BLACK BEAUTY™ restores rubber to like-new condition. Tires, side moldings and all rubber components will regain their original black look. Applying to door and trunk seals will prevent drying and cracking leading to water leaks. BLACK BEAUTY™ is a non-silicone formula and is harmless to painted surfaces.

### Directions:

1. Shake well before using. Make certain surface to be treated is clean and dry.
2. Spray BLACK BEAUTY™ directly onto surface. Also may be applied by spraying product onto a cloth first and then wiping evenly over the area to be treated.
3. To rejuvenate neglected tires, spray directly onto surface. Repeat application if more gloss is desired.
4. To renew rubber moldings and seals, wipe surfaces with a cloth dampened with BLACK BEAUTY™.

### Product Number and Packaging:

- #204132 - 1 quart
- #20411 - 1 gallon
- #20415C - 5 gallon

For complete product specifications, review the product SDS at [wellworthproducts.com](http://wellworthproducts.com).

### Storage:

Do not store in temperatures above 120°F (50°C). Do not puncture, incinerate or burn aerosol can. Do not place near sources of heat.

### First Aid Measures:

- EYE CONTACT: Flush eyes with cool water for at least 15 minutes, or flush with a buffered eye wash solution. If irritation continues, get medical attention.
- SKIN CONTACT: Wash with soap and water. Remove clothing; was before reuse.
- INHALATION: Remove to fresh air and ensure breathing.
- INGESTION: Drink large amounts of water or milk. Seek prompt medical attention.

ChemTrec (USA) 800-424-9300