




# DOT 4 BRAKE FLUID SUPER HEAVY DUTY



DOT 4 Super Heavy Duty Brake Fluid is for all types of automotive brake systems including drum, disc and ABS brakes where DOT 3 or DOT 4 is recommended. Can be mixed with all approved DOT 3 and DOT 4 brake fluids. Exceeds SAE Spec J1703, Federal Spec W-B680A, and conforms to Federal Motor Vehicle Standard 116 for DOT 4 brake fluids.

**Directions:**

FOLLOW VEHICLE MANUFACTURER RECOMMENDATIONS WHEN ADDING BRAKE FLUID. KEEP BRAKE FLUID CLEAN AND DRY. Contamination with dirt, water, petroleum products or other materials may result in brake failure or costly repairs. Clean all dirt from cylinder and surrounding area before removing reservoir cap.

**Product Number and Packaging:**

- #8073 - 12 oz.....24 per case
- #8074 - 32 oz.....12 per case

For complete product specifications, review the product SDS at [wellworthproducts.com](http://wellworthproducts.com).

**Storage:**

Store in a dry place. Store only in its original container. Keep contained clean and tightly closed.

**First Aid Measures:**

- EYE CONTACT: Immediately flush eyes with water for 15 minutes. If irritation persists, get medical attention.
- SKIN CONTACT: Remove contaminated clothing. Wash skin with soap. Wash clothing before reuse.
- INHALATION: Move person to fresh air; if effects occur, get medical attention.
- INGESTION: If a large amount (several ounces) has been swallowed, and if conscious, give two glasses of water. Induce vomiting. This should be done only by medical or first-aid personnel. Get medical attention.

ChemTrec (USA) 800-424-9300