



# RUB-R SHIELD™

## RUBBER UNDERCOATING



RUB-R-SHIELD's 100% rubber undercoating formula dries to the touch in just 15 minutes and is paintable in less than an hour. Leaves behind a flexible, abrasion-resistant coating that seals out road noise, dirt and moisture, and inhibits corrosion. Excellent adhesion on bare or painted metal and plastics. RUB-R-SHIELD™ accepts all automotive paints.

### Directions:

1. Make certain the surface to be coated is clean and dry.
2. SHAKE WELL BEFORE USING. Allow mixing ball to move freely for about one minute before using. Repeat this procedure periodically during application.
3. Hold can 10 to 12 inches from surface and apply a uniform coating while moving can rapidly. Note: Several thin coats are better than one heavy coating.
4. Remove overspray with Well Worth® TASK MASTER™ cleaning solvent or similar solvent material.
5. Clear valve by turning can upside down and spray until only pressure escapes.
6. Allow RUB-R-SHIELD™ to dry for 30-45 minutes before applying paint.

For complete product specifications, review the product SDS at [wellworthproducts.com](http://wellworthproducts.com).

### Storage:

Do not store in temperatures above 120°F (50°C). Do not puncture, incinerate or burn. Keep away from heat, sparks or open flame. Keep away from children.

### First Aid Measures:

- EYE CONTACT: Flush eyes with large amounts of water for 15 minutes. Get medical attention.
- SKIN CONTACT: Wash affected area thoroughly with soap and water. Remove contaminated clothing and wash before reuse.
- INHALATION: If affected, remove from exposure. Restore breathing. Keep warm and quiet.
- INGESTION: Do not induce vomiting. Get medical attention immediately.

### Product Number and Packaging:

#9008 – Net wt. 17.25 oz. V.O.C. Aer.....12 per case

ChemTrec (USA) 800-424-9300

800-890-7935

[www.wellworthproducts.com](http://www.wellworthproducts.com)