



SYNTHETIC GEAR OIL 75W-140 Premium

Directions:

For best results, change gear fluids often using SYNTHETIC GEAR OIL Premium 75W-140 for added protection.

Uses:

- Advanced Protection Formula Meets or Exceeds Required Specifications
- Reduces Moisture and Prevents Corrosion
- Requires No Additional Additive Packages for Limited Slip Applications

Packaging:

#805832 - 32 oz. Bottle......12 per case

For complete product specifications, review the <u>product SDS</u> at wellworthproducts.com.

Storage:

Keep containers closed when not in use. Do not handle or store near heat, flame or strong oxidants.

First Aid Measures:

- EYE CONTACT: Immediately flush eyes with plenty of cool water for at least 15 minutes. Do not let victim rub eyes.
- SKIN CONTACT: Wash with large amounts of soap and water. Remove contaminated clothing and wash before reuse. If irritation persists, get medical attention.
- INHALATION: Remove person to fresh air. If breathing is difficult give oxygen. Get medical attention.
- INGESTION: DO NOT induce vomiting. Give water to dilute. Do not give sodium bicarbonate, fruit juices, or vinegar. Get immediate medical attention.

ChemTrec (USA) 800-424-9300

HMIS HAZARD RATING

0-LeastA-Goggles1-SlightB-Goggles, Gloves2-ModerateC-Goggles, Gloves3-HighProtective Wear

Protection B

4-Extreme

NOTICE TO PURCHASER: Well•Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product. ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.