



TRANS VITAL™

Automatic Transmission Conditioner

Directions:

TRANS VITAL™ IS COMPATIBLE WITH ALL AUTOMATIC TRANSMISSION FLUID TYPES INCLUDING DEXTRON AND WORLD STANDARD.

- 1. TOP OFF: Add to ATF anytime fluid level permits. Do not overfill.
- 2. HIGH TEMPERATURE- HIGH LOAD: Add to ATF at 10.000 miles or before. Do not overfill.
- 3. Add at every fluid change.

NOTE: Properly dispose of used ATF at an EPA-approved disposal or recycling site.

Uses:

- Prolongs Transmission Life
- Protects Against Oxidation and Thermal Breakdown

Packaging:

WW 12 K Kit - TRANS VITAL™, TRANS KLEEN™ (#8009 - 12 oz.)

For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

No special handling procedures. Store at room temperature.

First Aid Measures:

- EYE CONTACT: Move away from exposure and into fresh air. Flush with water while holding eyelids open. If symptoms persist, get medical attention.
- SKIN CONTACT: Wash with soap and then flush with water. Remove clothing promptly and wash before reuse. If irritation persists, get medical attention.
- INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention.
- INGESTION: Get immediate medical attention. DO NOT induce vomiting. Give victim large amounts of water.

ChemTrec (USA) 800-424-9300

HMIS HAZARD RATING

0-Least **A**-Goggles 1-Slight **B**-Goggles, Gloves 2-Moderate C-Goggles, Gloves Protective Wear 3-Hiah Protection B 4-Extreme

Health..... 1 Flammability...... 1 Reactivity 0 Personal

NOTICE TO PURCHASER: Welle Worth Products, Inc. provides no warranty of any kind with respect to the product, whether express or implied including without limitation, the implied warranty of merchantability or fitness for any intended use or purpose; shall not be liable under any circumstances for any loss, damage, liability, injury or expense directly or indirectly resulting from, arising or related to the use or application of product; shall not be liable for consequential or incidental damages or loss of profits; and its liability shall be limited to replacement of the product. ALWAYS CONSULT MSDS for further details on precautions for safe handling and use.