

ALUMINATE

CONCENTRATED ALUMINUM CLEANER



Directions:

WARNING: ALUMINATE™ contains strong acids. Before using, READ ENTIRE LABEL AND MSDS SHEET for complete precautions for safe handling and use. Mix ALUMINATE™ as follows. Wire Wheels: use straight, do not dilute. Chrome, Mag and Aluminum Wheels: 1 part ALUMINATE™ with up to 10 parts of water.

- Wet entire wheel and surrounding area with water. Do only one wheel at a time. Test a spot on reverse side of wheel before using.
- 2. Spray directly on wheel. Allow to dwell for 1 minute only.
- 3. Rinse wheel and surrounding area with water.

NOTE: Use only on wire, chrome, mag, or aluminum wheel. Do not use on painted wheels.

Product Number and Packaging:

20471 - 1 gallon 20745C - 5 gallon 207432 - 1 quart For complete product specifications, review the product SDS at wellworthproducts.com.

Storage:

Avoid sparks and open flames. Keep contained closed when not in use. Do not allow product to freeze.

First Aid Measures:

- EYE CONTACT: Flush eyes with cool water for at least 15 minutes, or flush with a buffered eye solution. Seek medical attention.
- SKIN CONTACT: Flush skin with water for 15 minutes. Remove clothing, wash before reuse. Discard contaminated shoes and leather articles. Seek medical attention.
- INHALATION: Remove to fresh air and ensure breathing.
- INGESTION: Drink large amounts of water or milk. Rinse mouth with water. Seek prompt medical attention.

ChemTrec (USA) 800-424-9300