

## OIL GUZZLER **ENGINE DEGREASER**



## **Directions:**

- 1. For a thorough cleaning, make certain engine is warm
- 2. TURN IGNITION OFF BEFORE PROCEEDING.
- 3. Cover distributor cap and fresh air intake inlet with plastic sandwich bags or other waterproof material.
- 4. Liberally spray OIL GUZZLER™ on all areas to be cleaned.
- 5. Allow product to work for approximately 5 minutes before hosing off with a strong stream of water.
- 6. NOTE: TO CLEANGARAGE FLOOR AND DRIVEWAYS: Spray OIL GUZZLER™ liberally on all areas to be cleaned, wait 10 minutes before hosing off with a strong stream of water.

**Product Number and Packaging:** #1012 - Net wt. 15 oz. V.O.C. Aer......12 per case

For complete product specifications, review the product SDS at wellworthproducts.com.

Do not store in temperatures above 120°F (50°C). Do not puncture, incinerate or burn can. Keep away from heat, sparks or open flame.

## First Aid Measures:

- EYE CONTACT: Flush eyes with fresh water for at least 15 minutes. If irritation continues, get medical attention.
- · SKIN CONTACT: Wash skin with soap and fresh water. If irritation continues, get medical attention.
- INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.
- INGESTION: Get medical attention immediately. Do NOT induce vomiting.

ChemTrec (USA) 800-424-9300