



CERAMIC CARE WASH & WAX

Liquid Car Soap



Well Worth's CERAMIC CARE WASH & WAX is premium formulated to clean ceramic coated cars without deteriorating protective ceramic coatings. High tech glossifiers deliver a deep-down clean but leave painted, fiberglass and glass surfaces with a superslick high beading finish. Use CERAMIC CARE WASH & WAX on all exterior automotive surfaces to maintain a clean, shiny surface leaving paint clean and protected.

Directions:

DIRECTIONS: FOR BEST RESULTS, DO NOT WASH VEHICLE IN DIRECT SUNLIGHT.

1. Into a clean empty bucket, mix 4 ounces of CERAMIC CARE WASH & WAX with up to 5 gallons of water to develop a sudsy lather.
2. Using a wash mitt or sponge, wash vehicle completely beginning with the top, then the hood, trunk and sides.
3. Rinse thoroughly with clean water.
4. Towel or chamois dry.

Pro Tip: Use a high quality wash mitt such as Well Worth's Synthetic Pile Wash Mitt for best results

Product Number and Packaging:
#20011 - 1 Gallon

For complete product specifications, review the product SDS at wellworthproducts.com.

PRECAUTIONS: If medical advice is needed, have product container or label at hand. Read label before use.

FIRST AID: EYE CONTACT: If irritation occurs, cautiously rinse eyes with lukewarm, gently flowing water for 5 minutes, while holding the eyelids open. If eye irritation persists: Get medical advice/attention. SKIN CONTACT: Rinse/wash with lukewarm, gently flowing water and mild soap for at least 15 minutes or until product is removed. If skin irritation occurs or you feel unwell: Get medical advice/attention. INHALATION: Remove source of exposure or move person to fresh air and keep comfortable for breathing. INGESTION: Rinse mouth. Give two glasses of water. If you feel unwell or if concerned: Get medical advice/attention. Do NOT induce vomiting unless under the advice/direction of doctor/POISON CENTER.

STORAGE: Keep container(s) tightly closed and properly labeled. Store in cool, dry, well-ventilated areas away from heat, direct sunlight and incompatibilities. Store at temperatures between 40°F and 100°F. DISPOSAL: Dispose of in accordance with local/regional regulations.

Chemtrec (USA) 800-424-9300

800-890-7935

www.wellworthproducts.com