



ONE 4 ALL WITH LUBRICITY



ONE 4 ALL with LUBRICITY is an all season diesel fuel treatment that eliminates water and increases the lubricity (H.F.R.R) of the fuel to meet or exceed engine manufacturers recommended levels. This extra lubricity is vital to long term reliability and minimization of wear related failures. ONE 4 ALL with LUBRICITY also helps dissolve gums, varnishes, and carbon deposits that form in the fuel system leading to distorted injector spray patterns and/or component damage.

Directions:

READ SDS BEFORE USING.

For best results, use every time you fuel, adding contents to fuel tank(s) prior to fueling will ensure complete and proper mixing takes place. Treatment ratio is 1:1000 which equals 32 oz. per 250 gallons, or 1 gallon per 1000 gallons of fuel.

First time users can use a ratio of 1:500 which is 32 oz. per 125 gallons, or 1 gallon per 500 gallons of fuel to speed the cleaning process. When operating in extreme conditions (i.e. extreme cold, marine, high humidity, poor quality fuel), it is acceptable to use 32 oz. per 125 gallons (1:500) on a regular basis. ONE 4 ALL with LUBRICITY will eliminate approximately one half its own volume in water.

For complete product specifications, review the product SDS at wellworthproducts.com.

STORAGE: Keep away from sources of ignition. Store in a ventilated area in tightly closed containers equipped with means of preventing the product from reaching 140° F (100 °C).

DANGER: Combustible liquid. Contains petroleum distillates. Keep away from heat, sparks, or open flame. Harmful or fatal if swallowed.

FIRST AID: IF SWALLOWED: Rinse mouth. DO NOT INDUCE VOMITING. Call a physician or POISON CENTER immediately. IF ON SKIN: wash with soap and water. If irritation occurs, get medical advice/attention. IF IN EYES: Rinse cautiously with water for 15 minutes. Remove contact lenses if present and easy to do.

Product Number and Packaging:

#8033 - 32 oz Bottle.....12 per case

800-890-7935

www.wellworthproducts.com