

# **BIG RED**<sup>TM</sup> HEAVY DUTY GREASE



**GREASE** Waterproofs and Fights Corrosion Withstands High Temperatures &

Pressure NGER: Extremely flammable ARC WED Container: May Burst IF Heater Swallowed and Enters Airways Ma Wess or Durythess Calises SKIN IRRI

NET WT. 10.5 oz. (2989)

BIG RED<sup>™</sup> is a Lithium-complex base grease giving it a distinctive red color. As a thick heavy grease, BIG RED<sup>™</sup> out-performs lithium and calcium greases by standing up to extreme pressures and a wide range of temperatures up to 350°F. BIG RED<sup>™</sup> is 100% waterproof, resists acid, alkalis and salt. Use on many applications such as hinges, striker plates, cables, pullies, conveyors, and truck chassis, electric motor shafts, industrial bearings and heavy equipment.

## 800-890-7935

### Directions:

SHAKE CAN WELL BEFORE AND DURING USE. Spray in a wellventilated area away from heat, sparks, or open flame. Spray uniformly on surface to be lubricated. For greater accuracy, or when working in tight areas, use the attached extension tube. AFTER USING PRODUCT, ALWAYS CLEAR SPRAY NOZZLE BY INVERTING CAN AND SPRAYING FOR A FEW SECONDS UNTIL VALVE AND NOZZLE ARE CLEAR.

Product Number and Packaging: #5004 – 12 per case



CONTAINS: Heptane, Isobutane, Propane, Zinc Dithiophosphate

For more information, refer to the Well Worth Safety Data Sheet for this product, or call ChemTrec (USA) 800-424-9300

## KEEP OUT OF REACH OF CHILDREN

# www.wellworthproducts.com

**DANGER:** Extremely flammable aerosol. Pressurized container: may burst if heated. May be fatal if swallowed and enters airways, May cause drowsiness or dizziness. Causes skin irritation. Causes eye irritation.

**PRECAUTIONS:** Keep away from heat, hot surfaces, sparks, open flame and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapours/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of workplace. Wear protective gloves. Avoid release to the environment.

### FIRST AID:

EYE CONTACT: Check for and remove contact lenses. Immediately flush eyes with water for a minimum of 15 minutes keeping eyelids open. Consult a doctor if any irritation occurs. SKIN CONTACT: Remove contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes. Consult a poison control center or physician immediately. INHALATION: If inhaled, remove to fresh air. If not breathing, give artificial respiration and

INHALA I ION: If innaled, remove to fresh air. If not breathing, give artificial respiration and obtain immediate medical assistance.

INGESTION: Ingestion is unlikely to occur. If swallowed, do not induce vomiting because of risk of aspiration into the lungs. If aspiration is suspected obtain immediate medical attention.

**STORAGE**: Store locked up. Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate, or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store away from incompatible materials.