



CHAIN GANG™

CHAIN & CABLE LUBRICANT



CHAIN GANG™ with foaming action ensures maximum penetration. The water resistant formula reduces friction and wear, eliminates corrosion, and withstands extreme temperatures. Regular use extends the working life of equipment and improves performance.

Uses: Bicycles, motorcycles, cables, pulleys, chains, wire ropes, gears, linkages, sprockets and hinges.

Directions:

IMPORTANT: CHAIN GANG™ SHOULD NEVER BE APPLIED WHEN EQUIPMENT IS IN USE. PROPER PROTECTIVE MEASURES SHOULD BE IN PLACE TO ENSURE THAT EQUIPMENT CANNOT BE STARTED UNTIL TREATMENT IS COMPLETE. SHAKE CAN WELL BEFORE USING.

1. Spray CHAIN GANG™ at room temperature in a well-ventilated area.
2. Holding can in an upright position, spray CHAIN GANG™ generously to completely saturate and protect the surfaces being treated.
3. Re-apply as required.

Product Number and Packaging:
#5008 – 12 per case

For more information, refer to the Well Worth Safety Data Sheet for this product, or call ChemTrec (USA) 800-424-9300



DANGER: Do not spray near heat, sparks, or open flame. If swallowed do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY. Use with adequate ventilation. Avoid breathing mist or vapor. Deliberately concentrating or inhaling the vapor of the contents may be harmful or fatal. Do not puncture or incinerate (burn) container even after use. Do not store at temperatures above 120°F (50°C). Do not place near source of heat, radiator or in direct sunlight. High temperatures may cause the container to burst. If sprayed in eyes, flush thoroughly with water for 15 minutes. Remove contact lenses if present and easy to do, continue rinsing. For skin contact, wash thoroughly with soap and water. Contact physician if irritation persists.

Contains: Petroleum Distillates, Parafinic (CAS 64742-54-7), Petroleum Distillate, Naphthenic (CAS 64742-52-5), Propane (74-98-6), Isobutane (75-28-5) and n-Butane (CAS 106-97-8).

KEEP OUT OF REACH OF CHILDREN

800-890-7935

www.wellworthproducts.com