



EXCEL™ HEAVY-DUTY ANTI-SEIZE



EXCEL'S™ superior formulation is not affected by acids, solvents, oils, alkalis, gasoline, saltwater and other highly corrosive environments. Not affected by heat up to 1800°F. Maintains a high degree of electrical conductivity. For use on plastics, fiberglass and all metals including steel, aluminum, brass and copper. Acts as a high-quality lubricant for bearings, slides, etc.

APPLICATIONS: Manifold studs, cylinder head bolts, bushings, couplings, spark plugs, splines, drive chains, electrical conduit connections, gears, sprockets, lever pivots, rollers and hinges.

800-890-7935 www.wellworthproducts.com

DIRECTIONS: SPRAY PRODUCT ONLY AT ROOM TEMPERATURES ABOVE 60°F. Shake can vigorously for one minute after mixing ball begins to rattle. Make sure surface is cleaned of all dirt, grease, and other grime. Spray liberal amount from a distance of 8-10 inches. **IMPORTANT:** EXCEL™ REQUIRES CLEARING OF THE VALVE AFTER EACH USE TO PREVENT CLOGGING. INVERT THE CAN AFTER EACH USE AND SPRAY SHORT BURSTS TO CLEAR VALVE.

Product Number and Packaging:

#3010 – 12/CS



DANGER: Extremely flammable aerosol, pressurized container may burst if heated. May cause respiratory irritation. Harmful if swallowed. May be harmful in contact with skin. May cause damage to organs through prolonged or repeated exposure. Causes skin irritation. Causes serious eye irritation Suspected of causing cancer. Very toxic to aquatic life with long lasting effects.

PRECAUTIONS: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. Wash thoroughly after handling. Do not eat, drink or smoke when using the product. Do not handle until all safety precautions have been read and understood. Collect spillage.

CONTAINS: [CAS#]: Methylene Chloride [75-09-2], copper [7440-50-8], Butane [106-97-8], Propane [74-98-6], Isobutane [75-28-5].

FIRST AID: IF ON SKIN (OR HAIR): Take off immediately all contaminated clothing. Rinse skin with water or shower. If skin irritation occurs, get medical advice/attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell. IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF EXPOSED OR CONCERNED: Get medical advice/attention. intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal. If medical advice is needed, have product container or label at hand.

HEALTH HAZARDS: VAPOR HARMFUL. Use with adequate ventilation. Avoid breathing vapors and spray. To avoid breathing vapors or spray, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness increase fresh air, wear respiratory protection (NIOSH approved), or leave the area. Avoid contact with eyes and skin. Wash hands after using.

STORAGE AND DISPOSAL: In case of fire: Use water fog, dry chemical or carbon dioxide to extinguish. Keep cool. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Dispose of contents and container in accordance with all local, regional, national and international regulations.

For more information, refer to the Well Worth Safety Data Sheet for this product, or call ChemTrec (USA) 800-424-9300

KEEP OUT OF REACH OF CHILDREN - DO NOT TAKE INTERNALLY