




MY-T GREASE™



MY-T GREASE™ sprays on as a clear liquid to easily creep into tight areas, then sets up in minutes as a heavy duty grease. Resists vibration, extreme pressure, throw-off, squeeze-out and repeated exposure to water and saltwater. Withstands temperatures from -30°F to over 600°F. MY-T GREASE™ provides long lasting lubrication and protection. USES INCLUDE: Wire ropes, cables, open gears, door hinges, conveyors, marine, auto, truck and motorcycle applications.

800-890-7935

www.wellworthproducts.com

Directions:

SHAKE CAN WELL BEFORE AND DURING USE TO KEEP MY-T GREASE™ THOROUGHLY MIXED. Direct MY-T GREASE™ at area to be treated and spray on liberally. For greater accuracy, or when working in tight areas, use the attached extension tube.

Product Number and Packaging:
#5005 – 12 per case



For more information, refer to the Well Worth Safety Data Sheet for this product, or call ChemTrec (USA) 800-424-9300

KEEP OUT OF REACH OF CHILDREN

DANGER: Extremely flammable aerosol. Use with adequate ventilation. Avoid breathing spray mist or vapor. Harmful or fatal if swallowed and enters airways. Do not spray near heat, sparks, or open flame. Do not puncture or incinerate (burn) container even after use. Do not store at temperatures above 120°F (50°C). Do not place near source of heat, radiator, or in direct sunlight. High temperatures may cause the container to burst. IF SWALLOWED: Do not induce vomiting. CALL A PHYSICIAN IMMEDIATELY if you feel unwell. IF INHALED: Move person to fresh air and keep in comfortable breathing position. IF IN EYES: Flush thoroughly with water for 15 minutes. Remove contact lenses if present and easy to do, continue rinsing. IF ON SKIN: Wash thoroughly with soap and water. Contact physician if irritation persists. Take off contaminated clothing and wash before reuse. STORAGE: Store in a well ventilated place. Store locked up. Contains: Hexane (CAS 110-54-3), Paraffinic Petroleum Distillates (CAS 64742-65-0), Propane (74-98-6), Isobutane (75-28-5) and n-Butane (CAS 106-97-8).