




THUNDERBOLT™ PENETRATING OIL



THUNDERBOLT's™ formula works by attracting it to metals, rust and corrosion, working to free frozen parts quickly and easily. Thunderbolt™ FOAMS ON, TO STAY ON and won't run off. Keeps working even when exposed to high temperatures. Thunderbolt™ is formulated with a special lubricant that protects and lubricates metal surfaces even under demanding conditions.

Directions:

IMPORTANT: BECAUSE THIS PRODUCT IS FLAMMABLE, DO NOT SPRAY NEAR SPARKS OR OPEN FLAME OR ON HOT PARTS OR SURFACES.

SHAKE CAN WELL BEFORE USING. Spray Thunderbolt™ on frozen, rusted, or oxidized parts. Allow several minutes for Thunderbolt™ to soak and penetrate parts. Tapping the parts will help accelerate the penetrating action. In extremely tough situations, repeat above procedure.

Product Number and Packaging:
#5009 – Net wt. 15.75 oz. Aer.....12 per case



DANGER: EXTREMELY FLAMMABLE. Do not spray near heat, sparks, or open flame. If swallowed, do not induce vomiting. CALL PHYSICIAN IMMEDIATELY. Use with adequate ventilation. Avoid breathing spray mist or vapor. Deliberately concentrating or inhaling the vapor of the contents may be harmful or fatal. Do not puncture or incinerate (burn) container even after use. Do not store at temperatures above 120° F (50°C). Do not place near source of heat, radiator or in direct sunlight. High temperatures may cause the container to burst. If sprayed in eyes, flush thoroughly with water for 15 minutes.

Contains: Naphthenic Oil (CAS unknown), Kerosene (8008-20-9), Ethyl Acetate (147-78-6), Propane (74-98-6), Isobutane (75-28-5)

For more information, refer to the Well Worth Safety Data Sheet for this product, or call ChemTrec (USA) 800-424-9300.

KEEP OUT OF REACH OF CHILDREN