





EOA<sup>™</sup> fortifies all types of quality motor oils (including synthetic, standard, diesel) to maintain peak engine performance. EOA<sup>™</sup> stabilizes oil, prevents sludge formation and keeps engine and its components clean for extended engine life. Advanced zinc modifiers reduce wear and extend bearing life.

## 800-890-7935

## Directions:

Add  $EOA^{TM}$  to 4 or 5 quarts of motor oil at every oil change. Add to crankcase anytime oil level is low to fortify the motor oil. Do not overfill crankcase.

## Product Number and Packaging: #5020 – 24/CS

For more information refer to Well Worth® Safety Data Sheet. ChemTrec (USA) 800-424-9300

## KEEP OUT OF REACH OF CHILDREN



www.wellworthproducts.com

HARMFUL OR FATAL IF SWALLOWED. SKIN AND EYE IRRITANT.

**PREVENTION:** Do not handle until all safety precautions have been read and understood. Use personal protective equipment as required. Wash face, hands and any exposed skin thoroughly after handling. Wear eye/face protection.

**FIRST AID:** IF IN EYES: Flush with plenty of water for several minutes. Remove contact lenses. Get medical assistance.

IF ON SKIN: Wash skin with plenty of soap and water. Wash clothing before reuse.

IF INHALED: Remove victim to fresh air and keep at rest. IF SWALLOWED: Do NOT induce vomiting. Rinse mouth. Get medical assistance if symptoms occur.

**STORAGE:** Store away from incompatible materials. Odorous and toxic fumes may form from decomposition of this product if stored at temperatures above 133°F (45°C) for extended periods of time.