



EXCEL™ HEAVY DUTY ANTI-SEIZE



EXCEL™ Brush Top Anti-Seize and lubricating paste contains micro-size copper particles and graphite in a no-melt base. Protects against galling, seizing, corrosion and galvanic action when used during assembly. Excel™ is salt resistant and waterproof and will not evaporate, separate, harden or fuse to metals even when exposed to extreme heat, freezing temperatures, pressure, steam or water exposure. APPLICATIONS: Engine head bolts, brake lube assembly, spark plug, oxygen sensor threads, exhaust manifold studs, EGR fittings, starter and alternator bolts, and more!

800-890-7935


www.wellworthproducts.com

Directions:

For best results, surfaces must be clean and free of greases. Apply a light coating of product to parts. Assemble parts. Wipe away any excess compound.

Product Number and Packaging:

#6010 – 6/CS



DANGER: Contains Petroleum Oil (64742-54-7), Graphite Powder (7782-42-5), and copper (7440-50-8).

Avoid contact with skin and eyes.

Do not ingest.

For eye contact, flush with water for 15 minutes, call a physician.

For skin contact wash thoroughly with soap and water.

If swallowed do not induce vomiting, call a physician.

For inhalation, get fresh air.

For more information, refer to the Well Worth Safety Data Sheet for this product, or call Chemtrec (USA) 800-424-9300

KEEP OUT OF REACH OF CHILDREN