

**QUIK STICK**<sup>TM</sup> SPRAY ADHESIVE



Industrial Strength Aggressive Tack Permanent Bond Bonds Vinyl, Leather, Gaskets Headliners, Floor Carpets, Violstery Foram, Fabric, Paper Cardboard, Insulation, Insulation, Paper Cardboard, Insulation, Paper Cardboard,

USES SKINI IRRITATION, CAUSES SERIOUS PE IATION, MAY CAUSE DROWSINESS OR DUZANS REMELT FLAMMABLE ARENOSOL. CONTAIN US INDER PRESURE; MAY EXPLODE IF HEATED. Read cautions on rear panel QUIKSTICK<sup>™</sup> professional spray adhesive forms a strong permanent bond when used to attach vinyl, leather, polyurethane and foam rubber to metal, wood, fabrics and other surfaces. Although QUIKSTICK<sup>™</sup> becomes tacky almost instantly, the long bonding range allows repositioning up to 15 minutes later.

# 800-890-7935

#### **Directions:**

IMPORTANT: Always mask off where over-spray may occur. May affect some painted surfaces.

- 1. Shake can thoroughly before and during use.
- Make certain both surfaces to be bonded are clean and dry. Make certain temperature is above 60°F when applying Quikstick.
- Holding can about 6-8 inches away, apply two uniform and overlapping coats on both surfaces to be joined.
- Allow Quikstick to dry until tacky (1 to 3 minutes). Bond surfaces using firm and uniform pressure. Bond needs to be made within 15 minutes of Quikstick being applied.
- 5. When job is completed, clean valve by inverting can and spraying until only pressure escapes.
- Any over-spray or excess adhesive can be removed with either mineral spirits or alcohol.

NOTE: When a temporary bond is desired, or when working on porous materials, spray only one side and attach.

### Product Number and Packaging: #3004 – 12/CS

CONTAINS: Propane/Isobutane/N-butane, Petroleum Distillates, Methyl Acetate, Acetone, Cyclohexane.

For more information, refer to the Well Worth Safety Data Sheet for this product. Chemtrec (USA) 800-424-9300

### NOT FOR SALE IN CALIFORNIA

# www.wellworthproducts.com



DANGER: EXTREMELY FLAMMABLE AEROSOL. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. CAUSES SKIN AND SERIOUS EYE IRRITATION. MAY CAUSE RESPIRATORY IRRITATION, DROWSINESS AND DIZZINESS. MAY BE FATAL IF SWALLOWED AND ENTERS AIRWAYS.

**PREVENTION:** Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves, eye protection, face protection. Avoid breathing fumes, gas, mist, vapors, spray. Use only outdoors or in a well-ventilated area. Keep away from heat, sparks, open flames, hot surfaces – No smoking. Do not spray on an open flame or other ignition source. Pressurized container: Do not pierce or burn, even after use.

**FIRST AID:** IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice, attention. IF ON SKIN: Wash with plenty of soap and water. Take off contaminated clothing and wash it before reuse. If skin irritation occurs: Get medical advice, attention. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call POISON CENTER or doctor, physician if you feel unwell. IF SWALLOWED: Immediately call a POISON CENTER, doctor, physician. Do NOT induce vomiting.

**STORAGE:** Store locked up. Store in a well-ventilated place. Keep container tightly closed. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F **DISPOSAL:** Dispose of contents, container to an approved waste disposal plant.