



MASTER BLASTER™

INTAKE VALVE & COMBUSTION CHAMBER CLEANER



Drivability problems associated with carbon build-up are quickly and simply resolved with MASTER BLASTER™. Especially recommended for finely tuned fuel injected engines. Equally effective as a top engine cleaner for standard engines. Drivability problems such as knocking, pinging and after-dieseling are immediately improved as MASTER BLASTER™ disintegrates carbon deposits from piston crowns, cylinder heads and combustion chamber.

800-890-7935

www.wellworthproducts.com

Directions:

1. Start engine and bring up to operating temperature.
2. Adjust engine idle to between 500 and 750 RPM and remove PCV valve from engine. IF PCV valve is screwed into the engine, disconnect hose from PCV valve.
3. Feather MASTER BLASTER™ into hose. If PCV valve is too difficult to access, use a centrally located vacuum port.
NOTE: Failure to increase RPM's or feeding the material too fast into the combustion chamber could cause hydrolocking of the engine.
4. Shut engine off for 10 minutes to allow product to continue cleaning.
5. To complete the job, add a bottle of XCELERATE™ or POWER-UP™ to the tank. Restart the engine and drive.

Product Number and Packaging: #1034 – 12/CS

CONTAINS: Solvent Naphtha, Heavy Aromatic (64742-94-5), Propane (74-98-6), Oleic Acid (112-80-1), Isobutane (75-28-5), 2-Butoxyethanol (111-76-2), Ammonia Solution (7664-41-7).

Read Well Worth SDS before use. Chemtrec (USA) 800-424-9300

KEEP OUT OF REACH OF CHILDREN

STORE: Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place. Keep container tightly closed. Store locked up.

DISPOSAL: Dispose of contents/container in accordance with local/regional/national/international regulations. Collect spillage.



DANGER: EXTREMELY FLAMMABLE AEROSOL. Pressurized container: may burst if heated. Causes skin and eye irritation. May cause drowsiness or dizziness. May be harmful if swallowed and enters the airways. May cause damage to the liver and kidneys through prolonged or repeated exposure. Harmful to aquatic life with long lasting effects.

PREVENTION: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not spray on an open flame or other ignition source. Do not pierce or burn, even after use. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact during pregnancy/while nursing. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Contaminated work clothing must not be allowed out of the workplace. Avoid release to the environment.

RESPONSE:

IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER if you feel unwell.

IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

IF SWALLOWED: Immediately call a POISON CENTER. Do NOT induce vomiting.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.